

AE-TS32W



DIP32/TSOP32 specialized adapter for Flash memory.
Device package dimensions: 8 x 20 mm, 0.5 mm pitch.

Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

Adapter analogues supplied by third-party vendors:

Logical Systems: PA32TS20-OT

Adapter Wiring Diagram:

DIP-32	TSOP-32
1	9
2	10
3	11
4	12
5	13
6	14
7	15
8	16
9	17
10	18
11	19
12	20

13	21
14	22
15	23
16	24
17	25
18	26
19	27
20	28
21	29
22	30
23	31
24	32
25	1
26	2
27	3
28	4
29	5
30	6
31	7
32	8

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [phyton manufacturer](#):

Other Similar products are found below :

[AE-ISP-ST7](#) [AE-P44-P16](#) [AE-Q100-MAX2](#) [AE-Q32-STM8](#) [AE-Q48-I51](#) [AE-Q48-XC800](#) [AE-Q64-ATM128](#) [AE-Q64-LPC2000](#) [AE-Q64-STM32](#) [AE-SP20-P16](#) [AE-SP28-P5X](#) [AE-SP28U1](#) [AE-SP8U](#) [AE-TS32W](#) [AE-TS40W-2](#) [AE-TS56-16I-3](#) [AE-TS28](#) [AE-SC8/16US](#) [AE-SC28U1](#) [AE-Q48-STM32](#) [AE-Q48-HCS12](#) [AE-Q44-P33](#) [AE-P52-HC908](#) [AE-P44-PLD](#) [AE-P32-28](#) [AE-P20U](#) [AE-Q64-PIC30-1](#) [AE-P44-4096](#) [AE-Q44-PIC30](#) [AE-Q64-P658](#) [AE-Q64-STM8](#) [AE-QFN48U](#) [AE-SC32U](#) [AE-SOT23-24XX](#) [AE-SOT23-93XX](#) [AE-SS56-16AM](#) [AE-TS32N](#) [AE-TS40N](#) [AE-TS48-16](#) [AE-T44-P16](#) [AE-SS56-16I](#) [AE-QFN40U](#) [AE-Q64-XC800](#) [AE-Q64-PIC30-2](#) [AE-Q64-P33](#) [AE-Q64-HCS12](#) [AE-Q64-HC908-1](#) [AE-Q52-HCS12](#) [AE-Q48-STM8](#) [AE-Q44U](#)