




# Special tools "L" shape forming pliers

## PTR 30 LD



**PTR 30 LD:** Tool that forms the component wire in a L shape and cuts off the residual part. Steel thickness 3.0mm. Tool length 150 mm. ESD-safe handles




| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PTR 30 LD  | 150         | 3                  | 1.02               | 18                |

# Special tools "TO" forming pliers

## PN 5050D



**PN 5050D:** Special tool for the forming of central lead of TO 220 with 3.81mm pitch. Steel thickness 5.0mm. Tool length 155mm. ESD-safe handles.




| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PN 5050D   | 155         | 3                  | 1.30               | 16                |

## PN 5050/3D



**PN 5050/3D:** Special tool for the forming of central lead of TO 247 and TO 220, 5.08mm pitch. Steel thickness 5.0mm. Tool length 158mm. ESD-safe handles.




| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PN 5050/3D | 158         | 3                  | 1.30               | 16                |

## PN 5050/14D



**PN 5050/14D:** Special tool for the forming of central lead of TO 220, 3.0 mm pitch. Steel thickness 5.0mm. Tool length 158mm. ESD-safe handles.




| Order code  | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|-------------|-------------|--------------------|--------------------|-------------------|
| PN 5050/14D | 158         | 3                  | 1.30               | 16                |

## PN 5050/15D



**PN 5050/15D:** Special tool for the forming of central lead of TO 220, 2.54mm pitch. Steel thickness 5.0mm. Tool length 158mm. ESD-safe handles.



| Order code  | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|-------------|-------------|--------------------|--------------------|-------------------|
| PN 5050/15D | 158         | 3                  | 1.30               | 16                |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pliers & Tweezers](#) category:*

*Click to view products by [Piergiacomini](#) manufacturer:*

Other Similar products are found below :

[0031](#) [32750](#) [PN-5050/38D](#) [PG-TP-30D](#) [PG-DP-18-N](#) [G77015](#) [4-1532129-2](#) [77 12 115](#) [0037](#) [T0058765801](#) [571](#) [76C](#) [37 31 125](#) [RX 8130](#)  
[37 33 125](#) [DRP10N](#) [32 11 135](#) [36 12 130](#) [0036](#) [64 11 115](#) [0032](#) [6231-08](#) [PN 5050/19D](#) [PNI 5000](#) [TP 5000/15D](#) [TR 30 15 V](#) [TR 5000 PR](#)  
[TR 58 R A D](#) [00 20 08 US2](#) [13 01 614](#) [87 28 250 SBA](#) [INCP8](#) [30993](#) [011820101](#) [011830101](#) [003780032](#) [003780041](#) [134-69-160](#)  
[134-69-180](#) [135-49-VDE-190](#) [137-49-VDE-180](#) [137-49-VDE-200](#) [137-49-VDE-240](#) [137-69-180](#) [137-69-200](#) [137-69-240](#) [138-49-VDE-200](#)  
[138-69-200](#) [140-49-VDE-170](#) [140-49-VDE-205](#)