


2SD965ASQ

NPN Transistor

Features

- Low saturation voltage
- Large Collector Power Dissipation and Current

SOT-89



1. Base 2. Collector 3. Emitter

Marking: Q: AQ

R: AR

S: AS

Absolute Maximum Ratings

Ratings at 25°C ambient temperature unless otherwise specified.


Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	40	V
Collector Emitter Voltage	V_{CEO}	30	V
Emitter Base Voltage	V_{EBO}	7	V
Collector Current	I_C	5	A
Power Dissipation	P_D	750	mW
Maximum Junction-to-Ambient	$R_{\theta JA}$	167	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{STG}	-55 to 150	°C



Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.









Parameter	Symbol	Min.	Typ.	Max.	
DC Current Gain at $V_{CE} = 2\text{ V}$, $I_C = 500\text{ mA}$ Current Gain Group	Q R S H_{FE}	230	-	380	
		340	-	600	
		560	-	800	
at $V_{CE} = 2\text{ V}$, $I_C = 1\text{ mA}$		-	200	-	
at $V_{CE} = 2\text{ V}$, $I_C = 2\text{ A}$		150	-	-	
Collector Base Cutoff Current at $V_{CB} = 10\text{ V}$	I_{CBO}	-	-	0.1	μA
Emitter Base Cutoff Current at $V_{EB} = 7\text{ V}$	I_{EBO}	-	-	0.1	μA
Collector Base Breakdown Voltage at $I_C = 100\text{ }\mu\text{A}$	$V_{(BR)CBO}$	40	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 1\text{ mA}$	$V_{(BR)CEO}$	30	-	-	V
Emitter Base Breakdown Voltage at $I_E = 10\text{ }\mu\text{A}$	$V_{(BR)EBO}$	7	-	-	V
Collector Emitter Saturation Voltage at $I_C = 3\text{ A}$, $I_B = 0.1\text{ A}$	$V_{CE(sat)}$	-	-	1	V
Transition Frequency at $V_{CE} = 6\text{ V}$, $I_C = 50\text{ mA}$	f_T	-	150	-	MHz
Collector Output Capacitance at $V_{CB} = 20\text{ V}$, $I_E = 0$, $f = 1\text{ MHz}$	C_{ob}	-	-	50	pF




2SD965ASQ

NPN Transistor

Static Characteristic






Package Outline

SOT-89

Dimensions in mm



Ordering information

Device	Package	Shipping
2SD965ASQ	SOT-89	1000/Tape&Reel(7inches)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Pingjingsemi manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)