



400V N-ch Planar MOSFET

Lead Free Package and Finish


General Features

- RoHS Compliant
- $R_{DS(ON),typ.}=0.78\ \Omega @ V_{GS}=10V$
- Low Gate Charge Minimize Switching Loss
- Fast Recovery Body Diode

BV_{DSS}	$R_{DS(ON),Typ.}$	I_D
400V	0.78Ω	6.0A

Applications

- Adaptor
- Charger
- SMPS Standby Power



Ordering Information

Part Number	Package	Brand
PSP06N40	TO-220	
PSA06N40	TO-220F	

Absolute Maximum Ratings

$T_c=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	PSA06N40	PSP06N40	Unit
V_{DSS}	Drain-to-Source Voltage	400		V
V_{GSS}	Gate-to-Source Voltage	±30		
I_D	Continuous Drain Current	6.0		A
I_{DM}	Pulsed Drain Current at $V_{GS}=10V$	24		
E_{AS}	Single Pulse Avalanche Energy	200		mJ
P_D	Power Dissipation	25	75	W
	Derating Factor above 25°C	0.2	0.60	W/°C
T_L T_{PAK}	Maximum Temperature for Soldering Leads at 0.063in (1.6mm) from Case for 10 seconds, Package Body for 10 seconds	300 260		°C
T_J & T_{STG}	Operating and Storage Temperature Range	-55 to 150		

Caution: Stresses greater than those listed in the "Absolute Maximum Ratings" may cause permanent damage to the device.

Thermal Characteristics

Symbol	Parameter	PSA06N40	PSP06N40	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	5.0	1.67	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	100	62	



Electrical Characteristics

OFF Characteristics

$T_J = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	400	--	--	V	$V_{GS}=0V, I_D=250\mu A$
I_{DSS}	Drain-to-Source Leakage Current	--	--	1	μA	$V_{DS}=400V, V_{GS}=0V$
		--	--	100		$V_{DS}=320V, V_{GS}=0V, T_J=125^\circ\text{C}$
I_{GSS}	Gate-to-Source Leakage Current	--	--	+0.1	μA	$V_{GS}=+30V, V_{DS}=0V$
		--	--	-0.1		$V_{GS}=-30V, V_{DS}=0V$

ON Characteristics

$T_J = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
$R_{DS(ON)}$	Static Drain-to-Source On-Resistance	--	0.78	1.0	Ω	$V_{GS}=10V, I_D=3.0A$
$V_{GS(TH)}$	Gate Threshold Voltage	2.0	--	4.0	V	$V_{DS}=V_{GS}, I_D=250\mu A$
gfs	Forward Transconductance	--	5.0	--	S	$V_{DS}=15V, I_D=3.0A$

Dynamic Characteristics

Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
C_{iss}	Input Capacitance	--	500	--	μF	$V_{GS}=0V, V_{DS}=25V, f=1.0MHz$
C_{rss}	Reverse Transfer Capacitance	--	8.0	--		
C_{oss}	Output Capacitance	--	65	--		
Q_g	Total Gate Charge	--	14.5	--	nC	$V_{DD}=200V, I_D=6A, V_{GS}=0 \text{ to } 10V$
Q_{gs}	Gate-to-Source Charge	--	3.0	--		
Q_{gd}	Gate-to-Drain (Miller) Charge	--	6.5	--		

Resistive Switching Characteristics

Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
$t_{d(ON)}$	Turn-on Delay Time	--	8	--	ns	$V_{DD}=200V, I_D=6A, V_{GS}=10V, R_g=9.1 \Omega$
t_{rise}	Rise Time	--	10	--		
$t_{d(OFF)}$	Turn-Off Delay Time	--	25	--		
t_{fall}	Fall Time	--	15	--		



Source-Drain Body Diode Characteristics

$T_J=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Min	Typ.	Max.	Unit	Test Conditions
I_{SD}	Continuous Source Current ^[2]	--	--	6.0	A	Integral pn-diode in MOSFET
I_{SM}	Pulsed Source Current ^[2]	--	--	24		
V_{SD}	Diode Forward Voltage	--	--	1.5	V	$I_S=6\text{A}$, $V_{GS}=0\text{V}$
t_{rr}	Reverse Recovery Time	--	300	--	ns	$V_{GS}=0\text{V}$ $I_F=6\text{A}$, $di/dt=100\text{A}/\mu\text{s}$
Q_{rr}	Reverse Recovery Charge	--	850	--	nC	

Note:

[1] $T_J=+25^\circ\text{C}$ to $+150^\circ\text{C}$

[2] Pulse width $\leq 380\mu\text{s}$; duty cycle $\leq 2\%$.



Typical Characteristics

Figure 1. Maximum Forward Bias Safe Operating Area




Figure 2. Maximum Power Dissipation vs Case Temperature




Figure 3. Maximum Continuous Drain Current vs Case Temperature




Figure 4. Typical Output Characteristics





Figure 5. Maximum Effective Thermal Impedance, Junction to Case





Typical Characteristics(Cont.)

Figure 6. Maximum Peak Current Capability




Figure 7. Typical Transfer Characteristics




Figure 8. Typical Drain to Source ON Resistance vs Gate Voltage and Drain Current




Figure 9. Typical Drain to Source ON Resistance vs Drain Current





Figure 10. Typical Drain to Source on Resistance vs Junction Temperature





Typical Characteristics(Cont.)

Figure 11. Typical Theshold Voltage vs Junction Temperature




Figure 1.2 Typical Breakdown Voltage vs Junction Temperature




Figure 13. Typical Capacitance vs Drain to Source Voltage




Figure 14. Typical Gate Charge vs Gate to Source Voltage




Figure 15. Typical Body Diode Transfer Characteristics





Figure 16. Unclamped Inductive Switching Capability





Test Circuits and Waveforms




Fig. 1.1 Peak Diode Recovery dv/dt Test Circuit




Fig. 1.2 Peak Diode Recovery dv/dt Waveforms

Test Circuits and Waveforms (Cont.)




Fig. 2.1 Switching Test Circuit




Fig. 2.2 Switching Waveforms




Fig. 3.1 Gate Charge Test Circuit




Fig. 3.2 Gate Charge Waveform




Fig. 4.1 Unclamped Inductive Switching Test Circuit




Fig. 4.2 Unclamped Inductive Switching Waveforms



Disclaimers:

Perfect Intelligent Power Semiconductor Co., Ltd (PIP) reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to PIP's terms and conditions supplied at the time of order acknowledgement.

Perfect Intelligent Power Semiconductor Co., Ltd warrants performance of its hardware products to the specifications at the time of sale, Testing, reliability and quality control are used to the extent PIP deems necessary to support this warrantee. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

Perfect Intelligent Power Semiconductor Co., Ltd does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using PIP's components. To minimize risk, customers must provide adequate design and operating safeguards.

Perfect Intelligent Power Semiconductor Co., Ltd does not warrant or convey any license either expressed or implied under its patent rights, nor the rights of others. Reproduction of information in PIP's data sheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. Perfect Intelligent Power Semiconductor Co., Ltd is not responsible or liable for such altered documentation.

Resale of PIP's products with statements different from or beyond the parameters stated by Perfect Intelligent Power Semiconductor Co., Ltd for that product or service voids all express or implied warranties for the associated PIP's product or service and is unfair and deceptive business practice. Perfect Intelligent Power Semiconductor Co., Ltd is not responsible or liable for any such statements.

Life Support Policy:

Perfect Intelligent Power Semiconductor Co., Ltd's products are not authorized for use as critical components in life support devices or systems without the expressed written approval of Perfect Intelligent Power Semiconductor Co., Ltd.

As used herein:

1. Life support devices or systems are devices or systems which:
 - a. are intended for surgical implant into the human body,
 - b. support or sustain life,
 - c. whose failure to perform when properly used in accordance with instructions for used provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [PIP](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)