

# KARTA KATALOGOWA

## REEL EXTENSION CORD PB-HEAVY/D/K/...T/...L/H07RR-F/...K



**Technical data:**

Voltage:	250V~
Current:	16A
Max load (cable unrolled):	3680W
Max load (cable coiled):	1100W
Ingress Protection Code:	IP44
Plug type:	2P+Z
Socket type:	French
Cable type (T):	H07RR-F 3x1,5mm <sup>2</sup> H07RR-F 3x2,5mm <sup>2</sup>
Available cable length (L):	20m, 30m, 40m, 50m
Available cable color:	Red, Black
Socket type:	Fixed, non-rotating

**Recommended use:**

For powering portable receivers with a maximum load of 3680W. They are intended for use wherever there is a high exposure to mechanical damage (pulling, dragging, sliding, bending), in dry, damp and wet rooms and in open areas, they are used to connect industrial and agricultural devices, electric tools such as drills and circular saws, as well as portable engines or machines on construction sites, farms and shipyards, are suitable for use in cold stores, they can also be permanently laid as installation cables

Serwis gwarancyjny i pogwarancyjny prowadzi producent.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AC Power Leads](#) category:*

*Click to view products by [Plastrol](#) manufacturer:*

Other Similar products are found below :

[YP-61+YC12](#) [YP21A+YC13](#) [6601](#) [FTP-629Y603](#) [1700001947](#) [IL13-EU1-H05-3100-300-S](#) [P28976-M45](#) [BB-3271V86](#) [P29844-M5](#)  
[P29844-M10](#) [P28818-M6](#) [387005324](#) [387005325](#) [59903000000](#) [387007040](#) [IL13P-EU1-H05-3100-300](#) [PCAK2](#) [PPA00002-25F](#) [EM9169](#)  
[32004](#) [32002](#) [W-98979](#) [W-98980](#) [W-98983](#) [W-98987](#) [W-99183](#) [AK-RD-07A](#) [LPS275](#) [18049236](#) [LA0055](#) [HC-3C1.5MM-W-P](#) [NUFPWC-](#)  
[03PMMS-LC500](#) [NUF-MSAP-08BMMM-RJ](#) [BEST 053](#) [W-99469](#) [W2243](#) [W-99945](#) [W-99764](#) [W-98642](#) [W-98643](#) [W-99440](#) [W-97783](#) [W-](#)  
[99175](#) [W-97760](#) [W-99243](#) [M02411](#) [W-98692](#) [50078](#) [M01895](#) [AK-RD-06A](#)