



# Unfluxed Desoldering Braid

## 1830-1833

Desoldering braid (wick) is pre-fluxed copper braid that is used to remove solder, which allows components to be replaced and excess solder to be removed.

Techspray wick is available in static dissipative bobbins (except where indicated) for static sensitive environments.



### Use your own flux -- ideal for aqueous process

For customers who use water-soluble flux, or their own flux for aqueous processes.



Size chart:

Braid #	Color Code	Width (in)	Width (mm)
#1	White	0.035	0.9
#2	Yellow	0.055	1.4
#3	Green	0.075	1.9
#4	Blue	0.098	2.5

- Apply your own flux
- Ideal for aqueous fluxes
- Allows flux matching in process
- Exceeds MIL-F-14256, Type
- Anti-static spool (except where indicated)

## Product Packaging

1830-10F  
Unfluxed White #1 Braid - AS  
10'  
25 units/case



1831-10F  
Unfluxed Yellow #2 Braid - AS  
10'  
25 units/case



1832-5F  
Unfluxed Green #3 Braid - AS  
5'  
25 units/case



1833-10F  
Unfluxed Blue #4 Braid - AS  
10'  
25 units/case





### Chemical & Physical Properties

Appearance	
Odor	
Flash Point	
VOC (EPA)	
VOC (CARB)	
Boiling Point	
Density	

### Chemical Composition

CHEMICAL NAME	CAS #
Copper	7440-50-8

### Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

### Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

#### North America

Techspray  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

#### Europe

ITW Contamination Control BV  
Saffierlaan 5  
2132 VZ Hoofddorp  
The Netherlands  
+31 88 1307 400  
email: [info@itw-cc.com](mailto:info@itw-cc.com)

#### Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Desoldering Braid / Solder Removal](#) category:*

*Click to view products by [Plato](#) manufacturer:*

Other Similar products are found below :

[532505-2](#) [T0054487199](#) [T0054486999](#) [DP-CC](#) [STDC-102](#) [T0054465499N](#) [T0058741815N](#) [T0052921799N](#) [T0054465299N](#) [T0051320399N](#)  
[T0051351199](#) [4036S](#) [6961](#) [9057](#) [9970](#) [9976](#) [DS104](#) [DS115T](#) [DS117T](#) [DS204](#) [DS206](#) [DS60](#) [ETBB](#) [HE80](#) [MP135](#) [MP136](#) [MP137](#) [MP138](#)  
[MT6](#) [UTC234](#) [T0054460273](#) [T0053411299N](#) [R350\[1.5M\]1.5mm](#) [R350\[1.5M\]2.0mm](#) [17538](#) [S1069](#) [1811-5F](#) [1830-10F](#) [1824-5F](#) [50-3-100](#)  
[1813-5F](#) [1833-10F](#) [1810-25F](#) [1823-25F](#) [1824-25F](#) [0320705](#) [0320800](#) [0320903](#) [0321200](#) [0321300](#)