




Model 2142

Insulated Miniature Banana Jack







PANEL CUTOUT

MODEL NO.	COLORS AVAILABLE
2142-0	BLACK
2142-2	RED
2142-3	ORANGE
2142-4	YELLOW
2142-5	GREEN
2142-6	BLUE
2142-9	WHITE

FEATURES:

- Accepts miniature banana plugs.
- Mounts in panels up to .250" thick.

MATERIAL:

Banana Jack Insulation – Polycarbonate. Color: Black Panel Insulator – Polycarbonate. Color: Black Lockwasher, #8 Internal Tooth – Steel

Hex Nut, #8-32 – Brass Banana Jack Body – Brass

Finish:

Lockwasher #8 – Nickel plated Hex Nut - Nickel plated. Banana Jack Body - Gold plated.

RATINGS:

Operating Temperature: +115°C (+239°F) Max. Current: 5 Amperes.

ORDERING INFORMATION: Model 2142-*

*=Color Code – See Tabulation Block Sold in packages of 10.

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

USA: Sales: 800-490-2361 Fax: 425-446-5844 Technical Support: technicalsupport@pomonatest.com
Europe: 31-(0) 40 2675 150 International: 425-446-5500 Where to Buy: www.pomonaelectronics.com

Rev: 100 D1093937

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Plugs & Test Jacks category:

Click to view products by Pomona manufacturer:

Other Similar products are found below:

579-0400 66000-7 R644543000 R921923000 R921930000 R941344000 R948161000 R999351000 1408-4 1533-1 174-R825B-EX

NYS508-BU NYS508-O 1680 174-R819B-EX R644543003 R644543004 R644543020 R644543021 R921926000 R921931000

R921932000 R921934000 R929991000 R941460000 R941461000 R941463600 R941920600 R948160000 31B-2-RED 032-0016-023 105
1106-001 108-1000-106 108-2301-621 66001-9 7013 1395080-1 930166100 NYS508-GR NYS508-V NYS508-W NYS508-Y NYS511-R

BP30-2BR10-B PKG BP30-10-WT BP30-2BR-B PKG BP30Y-1 PKG R941049000 R941340000 R921922000