



### MATERIALS:

Body: Gold Plated Brass  
 Center Contact: Gold Plated Beryllium Copper  
 Dielectric: PTFE

### Finish:

Body: Tarnish Resistant  
 Center Contact: Gold Plated

### RATINGS:

Operating Temperature:  $-65^{\circ}\text{C}$  ( $-85^{\circ}\text{F}$ ) to  $+165^{\circ}\text{C}$  ( $+329^{\circ}\text{F}$ )  
 Operating Voltage: 1000 VRMS  
 Nominal Impedance: 50 Ohms

### ORDERING INFORMATION: Model 2455

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02''$  (.51 mm),  $.xxx = \pm .005''$  (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies. Made in USA

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:*

*Click to view products by [Pomona](#) manufacturer:*

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [M3933/25-36N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [7325-1512-000](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [7406-1521-005](#) [8527](#) [8547](#) [FS11V](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL71-9](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#)