



MATERIALS:

Shielded Housing: Extruded Aluminum, Alloy 6063-T5

Finish: None

Cover: 2 each, 2.03 (.080) thick Aluminum, Alloy #1100-H14

Finish: Clear anodized per MIL-A-8625

Cover Screws: 16 each #4-40 x 6.35 (1/4") Flat head, carbon steel with blue zinc plating.

RATINGS:

Operating Temperature: -55°C to +150°C (-67°F to +302°F)

Noise Rejection: Greater than 70 dB.

ORDERING INFORMATION: Model 3306

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Connectors](#) category:

Click to view products by [Pomona](#) manufacturer:

Other Similar products are found below :

[5739](#) [5752](#) [5757](#) [912](#) [MXHS83QE1000](#) [IB3-10-SP01](#) [1691](#) [CR-43](#) [M10X100](#) [4247](#) [MM126037](#) [3316](#) [5747](#) [5754](#) [86101-07A01](#) [5753](#)
[MM126511](#) [MM126527](#) [5760](#) [2375380-1](#) [134328](#) [4248](#) [5735](#) [MM126056](#) [MM126310](#) [MXHS83QE3000](#) [4320-01069-0](#) [SV225](#) [CS20MA](#)
[3296](#) [3302](#) [783538-01](#) [3602](#) [3719](#) [3728](#) [923835-WT-C](#) [4226](#) [4245](#) [4246](#) [4903](#) [MXFR01JA1000](#) [5734](#) [5740](#) [5744](#) [911](#) [4057](#) [BU-30212-0](#)
[CT3878-0](#) [CT3878-2](#) [CT3879-0](#)