



MATERIALS:

Body: Contact – Gold Plated Beryllium Copper, Spring – Stainless Steel

Insulation: Glass filled nylon.

Marking: “Pomona 3925”

RATINGS:

Operating Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 300 WVDC Max.

Operating Temperature: +102°(+216°F.) Max.

Current: 5 Amperes

ORDERING INFORMATION: Model 3925, 4176-02 & 5522

Standard Colors: Available in 10 colors: -0 Black, -2 Red, -3 Orange, -4 Yellow, -5 Green, -6 Blue, -7 Violet, -8 Gray, -9 White

Kit 5522 contains 10 pieces of 3925, one of each color.

Kit 4176-02 contains 2 pieces of 3925, one Black / one Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ± .005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pomona manufacturer](#):

Other Similar products are found below :

[5699-RED](#) [5741](#) [5744](#) [5952](#) [6273-C-36-0](#) [6283-C-60](#) [72961](#) [72977](#) [MG-B-36-BLK](#) [8007](#) [8021](#) [8029](#) [8030](#) [8037](#) [8055](#) [8059](#) [8060](#) [8061](#)
[8062](#) [8063](#) [8068](#) [8069](#) [1166-4-BLK](#) [HB-18-ORG](#) [HB-18-VIO](#) [HB-24-BRN](#) [HB-24-GRY](#) [HB-24-VIO](#) [HB-36-0](#) [HB-36-BRN](#) [HB-36-VIO](#)
[1236-8-BLK](#) [1370-24-2](#) [1370-60-RED](#) [AL-B-8-RED](#) [1546410](#) [B-18-3](#) [1614-0](#) [1614-RED](#) [EM5054-240](#) [1632814](#) [1693-18-BLK](#) [1743-12-RED](#) [1743-24-0](#) [1743-48-2](#) [1743-60-BLK](#) [1808-C-12](#) [1898083](#) [1908984](#) [1910576](#)