


# Model 4788Right Angle BNC FemalePC Mount



RECOMMENDED PC MOUNTING

#### **MATERIALS:**

Body: Tarnish Resistant Nickel Plated Brass Body Mounting Pins: Nickel Plated Brass Center Contact: Gold Plated Beryllium Copper Center Mounting Pin: Gold Plated Brass Dielectric: Teflon per L-P-403

#### **RATINGS:**


Operating Voltage: Hands free usage in controlled voltage environments: 500 Vrms maximum. *For CE compliance*: not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

Operating Temperature:  $-85^{\circ}F$  to  $+329^{\circ}F$  ( $-65^{\circ}C$  to  $+165^{\circ}C$ ). Nominal Impedance: 50 Ohms

### **ORDERING INFORMATION:** Model 4788

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com) For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Pomona manufacturer:

Other Similar products are found below :

 8915-1511-000
 89674-0827
 6001-7071-019
 6002-7051-003
 6002-7551-202
 6059674-1
 619550-1
 630059-000
 M39030/3-01N
 M3933/25 

 36N
 6500-7071-046
 6769
 CX050L2AQ
 7002-1542-011
 7004-1512-000
 7009-1511-004
 7010-1511-000
 7029-1511-060
 7101-1541-010

 7101-1571-002
 7105-1521-002
 7145-1521-002
 7203-1571-003
 7209-1511-011
 7210-1511-015
 7210-1511-019
 73137-5015
 73216-2241

 7325-1512-000
 73404-2300
 7405-1521-005
 7405-1521-005
 7406-1521-005
 8527
 8547
 FS11V
 8808-1511-001
 9049-9513-000
 9074-9513 

 000
 9101-9573-002
 910A205F
 9130-9573-002
 PL11SC-026
 PL375-33
 PL40-5
 PL71-9
 PL74C-221
 PL75MC-217
 PL803-7
 980-8666-005