



### FEATURES:

- Uses a special low-triboelectric cable which has noise attenuating layers surrounding the center conductor.
- The cable is ideal for low power, low frequency measurements.

### MATERIALS:

Body: Brass, Tarnish Resistant Plating, Center Contact: Gold Plated Brass

Dielectric: PTFE

Strain Relief: PVC molded directly to cable and connectors

Cable: 22 AWG, stranding 7 x 30 t.c., PVC insulated, 4.95 (.195) O.D.

Marking: "Pomona 4964-SS"

### RATINGS:

Voltage: Shield/Earth: 30VAC/60VDC Max.

Inner Conductor/Shield: 500VRMS Max.

Operating Temperature: +50°C. (+122°F.) Max.

Nominal Impedance: 50 Ohms

Recommended Frequency Range: DC to 10KHz

### ORDERING INFORMATION: Model 4964-SS-\*

\*- Standard Lengths: 12, 24, 26, 48, 60, 96, 120, 144, 180, 240, 300, 360 – Lengths other than those specified are available on special request.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Cable Assemblies](#) category:*

*Click to view products by [Pomona](#) manufacturer:*

Other Similar products are found below :

[573/2](#) [73-6311-6](#) [73-6352-10](#) [73-6353-3](#) [73-6364-6](#) [MDB1-9SH001](#) [MDM-100PH001L-A174](#) [MDM-15PH003L-K139](#) [MDM-21PH003L-K139](#) [MDM-21SH009L](#) [MDM-21SH010F](#) [MDM-51PH017K](#) [MDM-51PH028K-A174](#) [MH113-01SB1-MH1RP-0152](#) [MIKQ6-7SH076](#)  
[R285001001](#) [R288940005](#) [RF174-01RP1-03RP1-0110](#) [145111-05-12.00](#) [1661-C-24](#) [2192](#) [CA-628485-A43](#) [24P104C24J1-012](#)  
[24P104C24P1-006](#) [24P104C24P1-018](#) [24P203C24P2-006](#) [24P204C24J1-003](#) [9950-1100-23](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-50](#) [24P103C24P2-003](#) [25P203C25P2-003](#) [R284008001](#) [R285426000](#) [R288940008](#) [RF174-03RP1-01BR1-0200](#) [RF179-74BJ3-77RP1-0305](#) [4814-BB-24](#) [500-181-R-ACC](#) [MIKQ6-7SH023](#) [5260-72](#) [314-120](#) [JR4N1-CL1-6F](#) [JR4R3-CL1-4F](#)  
[JT2N1-CL1-1F](#) [JT2T1-CL1-6F](#)