



FEATURES:

- Supports 18 20 & 22 AWG wires.
- This in-line 2.0 (.080) dia. pin tip plug is ideal for making patch cords and field repairs
- Parts will accept 18, 20, 22 AWG wire, crimp or solder connection.
- A snap-on two piece design allows the wire to be crimped or soldered to the pin tip plug.

MATERIALS:

Material: Brass per QQ-B-626, Alloy 360, ½ Hard

Insulation: Flexible PVC.

Marking: "POMONA"

Finish: Nickel plated per QQ-N-290, Class 2, Sulfate process, 200/300 microinches.

RATINGS: (Independent of Wire)

Operating Temperature: +50°C. (+122°F.) Max.

Operating Voltage: 3000 VRMS

Current: 5 Amperes

ORDERING INFORMATION: Model 5173-*

*=Color, -0 Black, -2 Red

Ordering Example: 5173-2 Adapter Color is Red

Parts are packaged one to a bag, unassembled.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Pomona](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [2970-BLK](#) [30-443G](#) [1680](#)