

For data sheets / specifications of the kit individual components, visit the Pomona web site at: www.pomonaelectronics.com

FEATURES:

- ✓ Test leads with a right angle banana plug are ideal for use with hand held digital multimeter.
- ✓ Flexible test leads feature high strand count silicone wire for extreme flexibility and high temperature resistance.
- ✓ Banana plugs are molded directly to the wire for superior pull strength.
- ✓ A modular probe design allows probes, alligators and grabbers to fit directly onto the test leads for testing versatility.
- ✓ Test accessories conveniently store in the four-fold nylon pouch.
- ✓ Compatible with most multimeters that accepts safety style sheath banana plugs.
- ✓ CE Compliant; complies with IEC 1010-2-031 standard for hand held accessories.

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com



Model 5904A Deluxe Electrical DMM Test Lead kit CE

The items included with this product are certified to meet IEC 1010-2-031 safety requirements.


Les élements inclus avec ce produit sont certifies pour répondre à des exigences de sûrete du IEC 1010-2-031. Los items incluidos con este producto se certifican para resolver requisitos de seguridad del IEC 1010-2-031.

- Only IEC 1010 type shrouded test plugs should be used with IEC 1010 type jacks. NEVER INSERT A PROBE TIP WITH BANANA SPRING INTO A TEST ACCESSORY JACK THAT WILL BE USED AS A HAND HELD PROBING DEVICE

-Seuls les vérificateurs de tension renforcés de type IEC 1010 devraient être utilisés avec des jacks de type IEC 1010. NE JAMAIS INSERER DE BOUT DÉ SONDE ÁVEC RESSORT BANANE DANS UN JACK D'ESSAI D'ACCESSOIRES QUI SERA UTILISE COMME DISPOSITIF DE SONDAGE A MAIN.

-Se deben usar sólo tapones de prueba reforzados del tipo IEC 1010 con receptáculos de tipo IEC 1010. NUNCA INTRODUZCA UNA CLAVIJA CON UN MUELLE TIPO BANANA EN UN RECEPTACULO DE PRUEBA QUE A SU VEZ SE USE COMO APARATO DE PRUEBA MANUAL.





Double Insulation or Reinforced Insulation. Isolation Double ou Isolation Renforée. Aislamiento Doble o Aislamiento Reforzado.

Overvoltage Category I, II, III or IV. Surtension Categorie I, II, III ou IV. Sobretension de Categoria I, II III o IV. CAT



Caution! Refer to Accompanying Documents. Attention! Se Reporter aux Documentsjoints. ; Peligro! Consulte los Documentos Adjuntos.



Caution! Risk of Electric Shock. Attention! Risque de Choc Électrique. ¡Peligro! Riesgo de Sacudida Eléctrica.

ectronics ce PO Box 9090, Everett, WA 98206-9090 TEL: 800-490-2361

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

> Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

Rev: 002 D1113596

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Leads category:

Click to view products by Pomona manufacturer:

Other Similar products are found below:

795-2384-10-25 1301430020 15107 1510-24-105 15308 15408 15302 15307 15407 15409 BU-1149-A-36-0 BU-1481-E-12-0 BU-1481-E-24-0 1927617 2450 2524-A-60 LB1F-2R-RED LB1F-2R-YLW 2500 2524-A-48 2977-J-48 R948131000 380200 BU-1449-E-12-2 BU-1480-E-24-0 BU-1481-E-12-2 BU-1481-E-24-2 LB1F-2R-BLK LB1F-2R-BLUE LB1F-2R-WHT 6345 6432 EM3782-24-3# R948161002 R948160002 R948170002 R948171002 R948163002 973604100 934160101 934160100 R948174000 CT3269 CT3258 CT3158-100 HSPL 8568/AWG16/200/RT HSPL 8568/AWG16/200/SW 28.0119-10020 28.0127-05025 28.0127-20025