



FEATURES:

- Maxigrabber® test clip has been redesigned to meet IEC 1010-2-31. This is the latest international safety standard for test accessories.
- The long shaft is ideal for electronic, electrical and industrial applications where access to hard to reach high voltage test points is a requirement.
- The Tip Guard is Stainless Steel for tip durability..
- Safety sheathed jack mates to Pomona's 5907A, 5908A and 5909A Flexible Test Leads for Digital Multi-Meter interfacing.

MATERIALS:

Hook: Beryllium Copper, Nickel Plated
 Plunger, Housing: Polypropylene, Color: One Black, One Red
 Banana Jack: Body - Brass, Nickel Plated
 Tube: Polypropylene, Color: Yellow
 Compression Spring: Stainless Steel

RATINGS:

IEC 1010, Category III, P2 Compliant
 Operating Voltage: 1000 VRMS/DC
 Operating Current: 10 Amperes Max.

ORDERING INFORMATION: Model 5911A (Includes Set of one black and one red)

The Maxigrabber® Test Clip is also available in various Pomona DMM Test Kits.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies. Made in USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pomona manufacturer](#):

Other Similar products are found below :

[5699-RED](#) [5741](#) [5744](#) [5952](#) [6273-C-36-0](#) [6283-C-60](#) [72961](#) [72977](#) [MG-B-36-BLK](#) [8007](#) [8021](#) [8029](#) [8030](#) [8037](#) [8055](#) [8059](#) [8060](#) [8061](#)
[8062](#) [8063](#) [8068](#) [8069](#) [1166-4-BLK](#) [HB-18-ORG](#) [HB-18-VIO](#) [HB-24-BRN](#) [HB-24-GRY](#) [HB-24-VIO](#) [HB-36-0](#) [HB-36-BRN](#) [HB-36-VIO](#)
[1236-8-BLK](#) [1370-24-2](#) [1370-60-RED](#) [AL-B-8-RED](#) [1546410](#) [B-18-3](#) [1614-0](#) [1614-RED](#) [EM5054-240](#) [1632814](#) [1693-18-BLK](#) [1743-12-RED](#) [1743-24-0](#) [1743-48-2](#) [1743-60-BLK](#) [1808-C-12](#) [1898083](#) [1908984](#) [1910576](#)