


**Model 6481  
Test Connector Adapter Set**



**Features**

- 18-piece kit includes one red and one black set of each pin & socket size along with a set of 48" (1,2m) red and black test leads.
- Test adapters are ideal for rapid testing of the hard-to-get at contacts of multi-pin/socket connectors.
- Round pins and socket adapters.
- Flexible tip allows testing of adjacent contacts.
- Full insulation protects against shorting or contact damage.
- Test leads feature high strand count silicone wire for extreme flexibility and high temperature resistance.
- Model 4690 also fit 0.025in (0.63mm) sq. pins.

| Model | Contact Size | Type   | Current |
|-------|--------------|--------|---------|
| 4690  | 22 AWG .030" | Socket | 3 Amps  |
| 4691  | (.76mm)      | Pin    |         |
| 3560  | 20 AWG .040" | Socket |         |
| 3561  | (1.02mm)     | Pin    |         |
| 3562  | 16 AWG .063" | Socket |         |
| 3563  | (1.60mm)     | Pin    |         |
| 3564  | 12 AWG .093" | Socket |         |
| 3565  | (2.36mm)     | Pin    |         |

**Voltage Rating:**

For *CE compliance* and for personal safety, do not hold in hand when voltages exceed 30 Vrms/42.4 Vpk/60 Vdc or current exceeds 8A maximum. Maximum voltage for *hands free use*: 1000Vrms. Do not use on circuits where transient stresses can exceed the rated voltage.

**USA:** Sales: 800-490-2361  
 Technical Support: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)  
 Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500

**Where to Buy:** [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02''$  (.51 mm), .xxx =  $\pm .005''$  (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

**Model 6481**  
**Test Connector Adapter Set****Materials****Models: 3560, 3562, 3564 & 4690**

Insulation: Polyvinyl chloride (PVC)  
Banana Jack Body (upper connector)  
Material: Brass.  
Finish: Bright Tin plated  
Socket (lower connector):  
Material: Copper Alloy  
Finish: Gold over copper plate

**Models: 3561, 3563, 3565 & 4691**

Insulation: Polyvinyl chloride (PVC).  
Banana Jack Body (upper connector)  
Material: Brass.  
Finish: Bright Tin plated  
Pin (lower connector):  
Material: Brass  
Finish: Gold plated over electroless nickel.

**Model: 6358 Test Leads** (male to male)

Straight Sheath Banana Plug:

*Insulation:* Polypropylene, Color: One Black, One Red

Retractable Sheath Banana Plug:

*Compression Spring:* Stainless Steel*Tip:* Nylon, Color matches Color of Wire*Insulation:* Polypropylene Molded to the Plug and Wire. Color Matches Color of Wire.*Plug Body:* Brass, Nickel Plated*Banana Spring:* Beryllium Copper, Nickel Plated*Wire:* 18 AWG, 192 x 41 bare copper, Silicone Insulation, O.D. 0.144" (3,66mm), Color: One Black, One Red**Ratings****Models: 3560, 3562, 3564, 4690, 3561, 3563, 3565 & 4691 only**

Operating Voltage: For *CE compliance* and for personal safety, do not hold in hand when voltages exceed 30 Vrms/42.4 Vpk/60 Vdc. Maximum voltage for hands free use: 2500 Vrms Max. Do not use on circuits where transient stresses can exceed the rated voltage.

Operating Temperature: +55°C (+131°F) Max.

**(6358\* only):**

Conforms to IEC 61010-031

Operating Voltage: CAT III 1000V

Operating Temperature: +55°C (+131°F) Max.

Current: 10 Amperes

\* *Connectors with retractable insulation sleeves are only for connection to equipment that is NOT provided with terminals which accept fully insulated connectors. These connectors provide NO PROTECTION against electric shock. DO NOT use connectors with retractable insulation sleeves with hand-held probes.*

**Ordering Information**Model: **6481**

Kit contains one red and one black adapter of each model: 3560, 3561, 3562, 3563, 3564, 3565, 4690, 4691 and one set of Model 6358 test leads.

**USA:** Sales: 800-490-2361  
Technical Support: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)  
Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500

**Where to Buy:** [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Accessories - Other](#) category:*

*Click to view products by [Pomona](#) manufacturer:*

Other Similar products are found below :

[AO1026](#) [AO1035](#) [AO1051](#) [AO1059](#) [149116](#) [149118](#) [RS40](#) [RS41](#) [AO1030](#) [AO1032](#) [AO1036](#) [AO1058](#) [4742](#) [KTS288540](#) [11-32-2733](#)  
[00415](#) [00163](#) [PACC-ZD007](#) [700M20TH](#) [628824000](#) [MPT-VF](#) [B3](#) [15010A0A0100M0](#) [B3](#) [15050A0D01A2M0](#) [B3](#) [15060A0D0100M0](#) [98-](#)  
[CAL020](#) [VDV500-705](#) [68-020-01P](#) [CPAK8](#) [LCR-OPT-02](#) [UTM03](#) [XDS SOFT BAG](#) [1-1437358-1](#) [DME D110 T1](#) [LMLH 50](#) [FLUKE](#)  
[PM9082/001](#) [85392-12](#) [ST18/SMAM/SMAM/72](#) [HO720](#) [45025](#) [45028](#) [CT2300](#) [CC545](#) [VT-1000](#) [CT3041](#) [VS-AVT-CABLE-08](#) [6172A](#) [68-](#)  
[023-01](#) [67-023-01](#) [67-012-01](#) [15-3108](#)