

### Models 6737, 6738, 6739, 6740 - 75 Ω BNC Adapters BNC (F/F), BNC (F/F/F)-T, BNC (F/M/F)-T, BNC (M/M)



Model 6737 BNC (F/F)



Model 6738 BNC (F/F/F)



Model 6739 BNC (F/M/F)



Model 6740 BNC (M/M)


# Incorporate Pomona 75 Ω BNC adapters in your broadcast application designs


### **Features**


All connectors and adapters designed to 75  $\Omega$  for broadcast applications. Precision machined. PTFE.


#### **Materials**

- · Precision machined brass with tarnish resistant nickel plating
- Male center pin contacts are gold plated brass (20 micro inches). Female center contacts are gold plated heat treated beryllium copper.
- Insulation material is high density PTFE (not delrin).









### **Specifications**

Nominal impedance	75 Ω
Frequency	0-3 GHz
VSWR	1.10 max. 0-1 GHz 1.35 max. 1-3 GHz
Center contact resistance	1.5 mΩ
Insulation resistance	5000 ΜΩ
Number of insertions	500

Ratings: Voltage: 500 Vrms

Operating temperature: -85° F to +131 °F (-65 °C to

+155 °C) Max.

USA: Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

e-mail: technicalsupport@pomonatest.com

All dimensions are in inches. Tolerances (except noted):  $xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Pomona manufacturer:

Other Similar products are found below:

5916-1103-603 5918-1103-000 5919-1503-000 651A505 82-5552 9030-9523-502 A0407000 R114703000W R125704000 R125771001

R141710000W R141723161 R141730000 R143730700 R143770000 R161703000W R161730000 R161753000W R161791500W

R161791530W R201705000 R222705200 R222M40010W R223703180 R316754000 R405006000 R443162000 AD78TL HRM-513S

1996352-2 2157155-1 252169-75 AD158 2101130-1 252186 R114704000W R114720000W R125705001 R125705701 R125771000

R125771001W R125791501W R127704001 R127.870.001 R127872001 R141717000 R142710000 R142723000 R143703000 R143704000