

Model 6744 BNC (F/F) Adapter Panel Mount, Hermetically Sealed 75 Ω



6744 BNC (F/F) Panel Mount Hermetically Sealed-75 Ω

Use 75 Ω Pomona BNC connectors with panel or box broadcast applications

Features


- Hermetically sealed.
- Panel mount design.
- Precision machined. Gold plated contacts. Dielectric is PTFE (**not delrin**).


Materials

- Machined brass with tarnish-resistant nickel plating.
- Female center contacts are gold plated heat-treated beryllium copper.
- Precision machined high quality brass (not die cast).
- High quality machined PTFE dielectric.

Ordering Information

Model: 6744 BNC (F/F) Panel Mount Hermetically Sealed-75 $\boldsymbol{\Omega}$





PANEL CUTOUT

Specifications

Nominal impedance	75 Ω
Frequency	0-3 GHz
VSWR	1.10 max. 0-1 GHz 1.35 max. 1-3 GHz
Center contact resistance	1.5 mΩ
Insulation resistance	5000 ΜΩ
Number of insertions	500
Ratings: Voltage: 500 Vrms Operating temperature: -85 °F to +131 °F (-65 °C to +155 °C) Max.	

 USA:
 Sales: 800-490-2361
 Technical Support: 800-241

 2060
 Fax: 888-403-3360

 Europe:
 31-(0) 40 2675 150
 International: 425-446-5500

 e-mail:
 technicalsupport@pomonatest.com

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02^{\circ}$ (,51 mm), $.xxx = \pm .005^{\circ}$ (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Pomona manufacturer:

Other Similar products are found below :

 5916-1103-603
 5918-1103-000
 5919-1503-000
 651A505
 82-5552
 9030-9523-502
 A0407000
 R114703000W
 R125771001

 R141710000W
 R141723161
 R141730000
 R143730700
 R143770000
 R161703000W
 R161753000W
 R161791500W

 R161791530W
 R201705000
 R222705200
 R222M40010W
 R223703180
 R316754000
 R405006000
 R443162000
 AD78TL
 HRM-513S

 1996352-2
 2157155-1
 252169-75
 AD158
 2101130-1
 252186
 R114704000W
 R114720000W
 R125705001
 R125771000

 R125771001W
 R125791501W
 R127704001
 R127.870.001
 R127872001
 R141717000
 R1427120000
 R143703000
 R143704000