

Technical Data Sheet

Models 7158 , 7159, 7160 ¼" 2 & 3-Cond. Phone Jack, PC Board Mount



Model 7158 Horizontal 3-Conductor Jack, PC Board Mount

Ordering Information

Model: 7158, 7159, 7160



Model 7159 Horizontal 2-Conductor Jack, PC Board Mount



Model 7160 Horizontal 3-Conductor Jack, Solder Tabs

Use to mount securely with PC boards.

Features

- Connects with standard commercial phone plugs
- PC board mountable
- Stereo and mono versions
- Solderable
- 2 and 3 conductor versions

Materials

- Shell: Polyamide 6.6 15% GR
- Contacts: Nickel silver

 USA:
 Sales:
 800-490-2361
 Technical Support:
 800-241

 2060
 Fax:
 888-403-3360
 International:
 425-446-5500

 e-mail:
 technicalsupport@pomonatest.com
 International:
 425-446-5500

Where to Buy: www.pomonaelectronics.com

Specifications

Number of conductors	2 (Mono)-Model 7159 3 (Stereo)-Models 7158, 7160
Contact resistance	< 15 mΩ
Dielectric strength	1000 V dc
Insulations Resistance	1000 ΜΩ

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02^{\circ}$ (,51 mm), $.xxx = \pm .005^{\circ}$ (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Pomona manufacturer:

Other Similar products are found below :

 M444B
 6J1041A
 R4F
 E12BPKG
 ECP4PKG
 161-3502L-E
 MT333X
 171-0350-EX
 171-101A-EX
 171-3325-EX
 176S
 NC3MG-V

 NYS228G
 P10834
 P2380
 P2381X
 P2411X
 P2412
 P2724
 JM2PB-AU BULK
 9144
 S2674
 280L
 163-156N-2-E
 163-158N-2-E
 171-3308

 EX
 171-3500-E
 2501FT
 CMT335
 M10662
 330Q
 RJ5VI-S
 40116
 TM1R-AU
 TM2PBMJ-AU
 TM2PJ-AU
 BULK
 4803.1351

 49201
 49205
 TS3PBJ-AU
 TS3PBMJ-AU
 TT32BX
 54B
 40112
 40205
 XMT332B
 52170017-331
 570
 NM3