(Ø1.0) Ø.04"



# Model 73014 MCX PLUG STRAIGHT SEMI-RIGID, RG402



(11.8mm) (2.9mm) (2.9mm) (11.8mm) (2.9mm) (2.7 tg) (2.11" (2.9mm) (2.9mm) (2.9mm) (2.9mm) (2.9mm) (2.9mm)

Model 73014 MCX PLUG STRAIGHT SEMI-RIGID, RG402

Snap-on coupling and miniature size for fast connect and disconnect where space is limited.

#### **Features**

- DC 3 GHz bandwidth.
- 30% smaller than SMB connectors.
- Meets CECC 22220.
- Perfect for applications where space, weight, performance and ease of assembly are required.
- Precision machined and gold-plated for low loss.

#### **Materials**

- Body is machined brass with gold plating.
- Center contacts Plug is gold plated brass and Jack is gold plated beryllium copper.
- High quality PTFE insulators.
- Crimp Ferrules are gold or nickel plated copper.

### **Ordering Information**

Model: 73014

Description: MCX PLUG STRAIGHT SEMI-RIGID,

RG402

USA: Sales: 800-490-2361

Technical Support: technicalsupport@pomonatest.com

Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

Where to Buy: www.pomonaelectronics.com

### **Specifications**

opcomoations		
Impedance	50 Ω	
Frequency Range	DC - 3 GHz	
VSWR	1.35 max.	
Working Voltage	170 Vrms max.	
Dielectric withstand voltage	750 Vrms	
Center / Outer contact resistance	5 / 2.5 mΩ	
Number of insertions	500 cycles min.	
Insulation resistance	1,000 MΩ min.	
Temperature Range	-55° C to 155° C, -67° F to 311° F	

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. D2003450 REV 001




# Model 73014 MCX PLUG STRAIGHT SEMI-RIGID, RG402

#### **Cable Types and Crimp Die Information**


Connector Model #	Cable Groups	Crimp Die Cavity Size for Outer Ferrule
73014	RG402	.151 (3.8)

#### **Cable Assembly Instructions**

1. CUT CABLE END EVENLY AND PERPENDICULAR.




2. STRIP CABLE JACKET SPECIFICATION LENGTHS.



RECOMMENDED STRIP LENGTHS

3. CRIMP CENTER CONTACT TO CABLE CENTER CONDUCTOR.



4. SLIDE CONNECTOR BODY OVER CENTER CONTACT AND JACKET.



**USA:** Sales: 800-490-2361

 $\label{thm:component} \textbf{Technical Support} \\ \underbrace{\textbf{technical support@pomonatest.com}}_{} \\ \\ \\ \underline{\textbf{technical support@pomonatest.com}}_{} \\ \\ \\ \underline{\textbf{technical support@pomonatest.com}}_{} \\ \\ \underline{\textbf{technical support@pomonatest.com}}_{} \\ \\ \underline{\textbf{technical support@pomonatest.com}}_{} \\ \\ \underline{\textbf{technical support@pomonatest.com}}_{} \\ \underline{\textbf{t$ 

Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

D2003450 REV 001

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Pomona manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N M3933/25-36N 6500-7071-046 6769 CX050L2AQ 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7105-1521-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 7325-1512-000 73404-2300 7405-1521-005 7405-1521-802 7406-1521-005 8527 8547 FS11V 8808-1511-001 9049-9513-000 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL71-9 PL74C-221 PL75MC-217 PL803-7 980-8666-005