

FTPC100V-D series

100W LED Triac Dimmable Switching Power Supply (CV)



■ Features:

- Constant voltage design
- Protections: Short circuit / Overload / Over temperature
 - AC phase cut (leading or trailing edge) dimmable
 - Cooling by free air convection
- Compliance to worldwide regulations for lighting



⊙ ELECTRICAL SPECIFICATION

MODEL	FTPC100V12-D	FTPC100V24-D
OUTPUT		
Rated Voltage	12V	24V
Rated Current	8.33A	4.17A
Current Range	0 ÷ 8.33A	0 ÷ 4.17A
Rated Power	100W	100W
No Output Voltage (max.)	12.6V	25.2V
Line Regulation	± 1%	
Load Regulation	± 1%	
Voltage Tolerance [3]	± 3%	
Ripple & Noise (max.) [2]	300mV _{p-p}	
Setup, Rise Time [4]	500ms, 100ms / 230VAC at full load	
Hold up Time (typ.)	10ms / 230VAC at full load	
INPUT		
Voltage Range	220 ÷ 240VAC	
Frequency Range	47 ÷ 63Hz	
Power Factor (typ.)	PF > 0.9 / 230VAC at full load	
Efficiency (typ.)	85%	
AC current (typ.)	<1A / 230VAC	
Inrush current (max.)	<75A / 230VAC(25°C)	
No Load Power Consumption (max.)	< 1W	
DIMMING		
Dimming Range	1 – 100% of rated output current	
Suitable dimmers	Triac dimmers (leading or trailing edge) compatible with capacitive or inductive load	

FTPC100V-D series

100W LED Triac Dimmable Switching Power Supply (CV)



PROTECTIONS

Over Current	Range: 110 ÷ 140% Type: hiccup mode. Recovers automatically after fault condition is removed.
Short Circuit	Type: hiccup mode. Recovers automatically after fault condition is removed.
Over Temperature	Range: 110°C ± 10°C Type: shut down output voltage. Re-power on to recovery.

WORKING ENVIRONMENT

Working Temperature	-20°C ÷ +45°C
Working Humidity	45 ÷ 85% RH non-condensing
Storage Temperature and Humidity	-30°C ÷ +70°C, 10 ÷ 95% RH non-condensing

SAFETY AND EMC REGULATIONS

Safety Standards	Compliance to EN61347-1, EN61347-2-13 , EN 62493
Withstand Voltage	IN/OUT: 3.75kVAC
EMC Emission	Compliance to EN55015
EMC Immunity	Compliance to EN61547
Harmonic Current	Compliance to EN61000-3-3; EN61000-3-2

OTHERS

Dimensions	200 x 63 x 30mm (L x W x H)
Weight and Packing	0.45kg; 25pcs./box; box dimensions: 34 x 20.5 x 18.5cm


1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

FTPC100V-D series

100W LED Triac Dimmable Switching Power Supply (CV)




© MECHANICAL SPECIFICATION



PIN ASSIGNMENT

No.	Assignment	No.	Assignment
1	Input: AC/N	3	Output: U _{OUT+}
2	Input: AC/L	4	Output: U _{OUT-}

© SUGGESTED CONNECTION DIAGRAM WITH DIMMER



SUITABLE DIMMERS

HAGER-WBMD400TO

CLIPSAL 32E450LM

NIKO 310-01900

LEGRAND 78401

RECOM REDIM07

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Power Supplies](#) category:

Click to view products by [POS manufacturer](#):

Other Similar products are found below :

[PIFC-K250F](#) [PITB-K222A](#) [AC-A60VD24H2.5](#) [ALD-514012PJ134](#) [PWD-60-1-70-P](#) [ESS030W-1050-21](#) [BPOXL 4-12-035](#) [ESS010W-0180-42](#) [ESS010W-0350-24](#) [ESS010W-0200-42](#) [ESM060W-1400-42](#) [ESS010W-0500-12](#) [SLM140W-1.05-130-ZA](#) [ESS015W-0700-18](#) [HVG-240-54AB](#) [OTE 25/220-240/700 PC](#) [OT FIT 30/220-240/700 CS](#) [DAL30W-0600-42-T](#) [HVG-320-48AB](#) [CNB30W-0600-42-CAS](#) [87500757](#) [I-SELECT 2 PLUG 2100MA BL](#) [LCU 48V 75W DC-STR FO](#) [LC 45 W 500-1400 MA FLEXC SC EXC](#) [I-SELECT 2 PLUG 2000MA BL](#) [LC 50/200-350/170 FLEXCC LP SNC3](#) [LCO 14/100-500/38 O4A NF C EXC3](#) [LC 28W 300-700MA 42 FLEXC NF SC EXC3](#) [LC 44/1050/42 FIXC SRL ADV2](#) [LCA 60W 900-1750MA ONE4ALL C PRE](#) [LC 8/180/44 FIXC SR SNC2](#) [LC 19/200-350/54 FLEXC LP SNC4](#) [BXDR-PS-75BS-E116D-01-A](#) [LC 30/500/54 FIXC SR SNC2](#) [LCA 60W 24V ONE4ALL SC PRE SP](#) [LC 60W 75-330MA 310V FLEXC NF H16 EXC4](#) [LC 8/180/42 FIXC PC SR SNC2](#) [LC 10/350/29 FIXC SR SNC2](#) [LC 25/500/43 FIXC SR SNC2](#) [LC 50/100-400/140 PO4A NF H16 PRE3](#) [LC 25/600/42 FIXC SRL ADV2](#) [LCO 24/200-1050/39 NF C ADV3](#) [ELEMENT 35/220...240/900 G3](#) [LC 25W 350-1050MA FLEXC SR EXC](#) [LC 35W 24 ONE4ALL IP PRE](#) [BXDR-PS-25BS-E107D-01-A](#) [LC 17W 250-700MA FLEXC SR EXC](#) [LC 15W 350MA FIXC C SNC](#) [LC 14W 700MA FIXC PC SR SNC2](#) [LC 200W 24V SC SNC](#)