

# DIN100W12

12V/100W Din Rail Power Supply



## ■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
  - Isolation class II
- Can be installed on DIN Rail TS-35/7 or 15
  - MTBF 200.000 h

## ELECTRICAL SPECIFICATION

SELV

MODEL	DIN100W12					
<b>OUTPUT</b>						
Rated Voltage	12V					
Rated Current	8.3A					
Current Range	0 ÷ 8.3A					
Rated Power	100W					
No Output Voltage (max)	12.6V					
Voltage Adjustment Range [6]	10.7 – 13.5V					
Line Regulation	± 0.5%					
Load Regulation	± 1%					
Tolerance [3]	± 5%					
Ripple & Noise (max.) [2]	150mVp-p					
Setup,Rise Time [4]	max. 400ms, max. 30ms / 230VAC at full load					
Hold up Time (typ.)	50ms at full load and 230VAC nominal line					
<b>INPUT</b>						
Voltage Range	180 ÷ 264VAC					
Frequency Range	47 ÷ 63Hz					
Inrush current (max.)	40A at 230VAC cold start at 25°C					
Efficiency (typ.)	86.93% - Average (25%+50%+75%+100%)/4					
AC Current (typ.)	1.3A / 230VAC					
Leakage current	<1.5mA at 50/60Hz 240VAC INPUT					
Max. No. Of PSU on Circuit Breaker	B10	B16	C10	C16	D10	D16
	5	8	5	8	11	17
No load Power Consumption (max.)	<0.5W					

# DIN100W12

12V/100W Din Rail Power Supply



## PROTECTIONS

<b>Over Current</b>	Range 120 ÷ 200% Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Short Circuit</b>	Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Over Voltage</b>	16 - 24V Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Over Temperature</b>	Range: NTC detect Type: shut down output voltage. Re-power on to recovery.

## WORKING ENVIRONMENT

<b>Working Temperature</b>	-20°C ÷ +50°C, ambient derate each output at 4.0% per degree from 50°C to 60°C
<b>Operating humidity</b>	5 ÷ 95% RH (non-condensing)
<b>Storage Temperature and Humidity</b>	-40°C ÷ +85°C, 5 ÷ 95% RH (non-condensing)

## SAFETY and EMC REGULATIONS

<b>Safety Standards</b>	Compliance to EN 62368-1
<b>Withstand Voltage</b>	IN/OUT: 3kVAC, IN/GND: 2kVAC, OUT/GND: 0.5kVAC
<b>EMC Emission</b>	Compliance to EN55032
<b>EMC Immunity</b>	Compliance to EN55035
<b>Harmonic Current</b>	Compliance to EN61000-3-2; EN61000-3-3


## OTHERS

<b>Dimensions</b>	100 x 93 x 56mm (L x W x H)
<b>Weight and Packing</b>	329g; 30pcs./box; weight box and dimensions: 10.3kg; 33.5 x 23.6 x 35.2 cm

## MECHANICAL SPECIFICATION

### PIN ASSIGNMENT

NO.	Assignment
1	Input: AC/N
2	Input: AC/L
3,4	Output: U <sub>OUT</sub> +
5,6	Output: U <sub>OUT</sub> -
7	LED indication for power on
8	U <sub>OUT</sub> adjustment




# DIN100W12

12V/100W Din Rail Power Supply



## MECHANICAL SPECIFICATION:



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIN Rail Power Supplies](#) category:*

*Click to view products by [POS manufacturer](#):*

Other Similar products are found below :

[PS-3015](#) [DVP01PU-S](#) [DVPPS01](#) [PS-C24024](#) [ADNB040-24-1PM-C](#) [SS14011524](#) [PSW-12024](#) [PSC-6024](#) [S8T-BUS03](#) [PS-S4024](#) [PS-10024](#)  
[PS-C12024](#) [PS-C48024](#) [PS-C480P24](#) [PSC-2024](#) [PSC-4048](#) [PSC-15124](#) [PSC-48148](#) [TRIO-PS-2G/1AC/12DC/5/C2LP](#) [PSS18/24/0.75](#) [PSD-](#)  
[A120W12](#) [NDR-7524](#) [AMED75-48SJZ](#) [787-1007](#) [1SVR427043R1200](#) [50995](#) [50903](#) [50997](#) [EL50-D](#) [18924-9989](#) [50996](#) [HDN-3024](#)  
[ISED-120-24](#) [1335699](#) [1335698](#) [SPE3103U](#) [SPM3051](#) [P4305-USB](#) [SPE6053U](#) [DT30P5](#) [SPM6053](#) [POS DIN30W24](#) [SPB-015-12](#) [EL50-B](#)  
[50905](#) [DRB240-48-1](#) [CFM50S360-SD](#) [POS DIN30W15](#) [POS MDIN60W12](#) [18924-9988](#)