



ProLED-1W-CC100

Professional Led Modules; **3-8CM** 3D double-sided lightboxes



■ Features:

- luminous efficacy 167 lm/W
- for indoor and outdoor use
- 20 pcs in chain



UK
CA

CE

TECHNICAL DETAILS



MODEL	ProLED-1W-CC100
Supply voltage	12V DC
Power consumption per module	0.36W
Chain power consumption	7.2W
Current consumption per module	30mA
LED diodes	LumiLEDs - 2835
Quantity of LEDs	1
Light color	White (~7000K)
Luminous flux	60lm (W)
Luminous flux density	167lm (W)
Color rendering index - CRI	≥80
Beam angle	175°
Current stabilization	No
Dimming	Yes
Module dimensions (L x W x H)	26 x 16 x 11mm
Cable length	74mm
Number of modules in 1m	10
Box weight	16kg
Packing	Chain – 20pcs / Bag – 100pcs / Box – 2800pcs
Montage	Adhesive tape / mounting screw
Lifetime	L70B50 > 50000h
Working temperature	-25°C ÷ 60°C
IP protection	IP67
Warranty	7 years




ProLED-1W-CC100

Professional Led Modules; **3-8CM** 3D double-sided lightboxes



Dimensions



Connection diagram

One-side power input:



Maximum number of modules 20 pcs

Two-side power input:




Maximum number of modules 40 pcs


It is acceptable to connect multiple chains in parallel, as long as the power supply provides sufficient power

Light color / CCT

Light color




Packing



Chain
20 pcs



Bag
100 pcs



Box
2800 pcs




ProLED-1W-CC100

Professional Led Modules; **3-8CM** 3D double-sided lightboxes




Application



$$\text{optical performance proportion} = \frac{D}{P} = 1 : 1.3$$

Overall micro lens design can improve the lens uniformity performance.



Energy label / Beam Angle

ENERGY


MW LIGHTING

MW-MLD-3030-1W-LENS v.2

A
B
C
D
E
F
G

2 kWh/1000h

2019/2015



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Bars and Arrays](#) category:

Click to view products by [POS manufacturer](#):

Other Similar products are found below :

[LTL-2755Y](#) [LF2B-D3P-BTHWW2-1M](#) [SSA-LXB10GW-18751](#) [SSA-LXB10YW](#) [SSA-LXH1025I1G7XXD](#) [HLMP2300](#) [LTL-2450Y](#) [LTL-2855G](#) [HLMP2655](#) [SSB-LX2301SIW](#) [TOS-4102BR-N](#) [SSA-LXB10-IYG8W-1](#) [LTL-57173HR](#) * [LPB-R0112051S](#) [SSA-LXB525-I1G3I1D](#) [MW-MLD-2835-3W-LENS V,2](#) [MW-MLD-2835-1W-LENS](#) [OSWSW51006B-5V](#) [PROLED-MINI-3W-CC100](#) [MW-MLD-2835-3B-LENS](#) [OSWM43-K4W](#) [PROLED-MINI-2W-CC70](#) [OSWM43-G5W](#) [MW-MLD-2835-2W-LENS V,2](#) [OSWSM51006B-5V](#) [OST1MC5A31A-W1V](#) [WL 30 W](#) [PROLED-3W-CC220](#) [MW-MLD-HE-3W-LENS170](#) [WL 20 W](#) [OSWM43-W5W](#) [57844](#) [113162000-00660681](#) [49983](#) [MW-MLD-HE-1WW-LENS170](#) [OSWM43-B6W](#) [MW-MLD-HE-2W-LENS170](#) [OSWM43-B5W](#) [OSWM43-Y5W](#) [MINIOVAL-1WW](#) [ALUSTAR-G2-NA-SC590-1A-54](#) [LTA-1000E](#) [LTL-57173HR](#) [1330.0001](#) [1330.0003](#) [1330.0009](#) [KB-2855SGW](#) [KB-B100SURKW](#) [L-1043GDT](#) [L-875/4SRDT](#)