



# UQS-COB-8W-W-24V

Professional Led Strip, 8W/m



## ■ Features:

- Uniform lighting
- Uniform light line and high luminous intensity
- 3 years warranty

6500K  
WHITE




## TECHNICAL DETAILS

| MODEL                               | UQS-COB-8W-W-24V   | EPREL |
|-------------------------------------|--|-------|
| Supply voltage                      | 24V ± 0.5Vdc   |       |
| Power                               | 8W/m (40W/reel)  |       |
| Current                             | 0.33 A/m (1.65A/roll)  |       |
| Power per reel                      | 40W  |       |
| Color temperature                   | 6500K  |       |
| Beam angle                          | 180°   |       |
| Luminous flux                       | 880 lm/m (4400lm/roll)   |       |
| CRI                                 | >90  |       |
| Maximum length for one sided supply | 5m   |       |
| IP protection degree                | IP20   |       |
| Working temperature                 | -20°C ÷ 50°C   |       |
| Storage temperature                 | -30°C ÷ 80°C   |       |
| LED QTY                             | 320 LEDs/m (1600 LEDs/reel)  |       |
| Width PCB                           | 8mm  |       |
| Cut section                         | 50mm   |       |
| Connection wire                     | 2 x AWG20 (0.52 mm <sup>2</sup> ) stranded wire, length = 360 mm: V+: red; V-:black. |       |
| Dimensions (L x W x H)              | 5004 x 8 x 2.2 mm  |       |
| Packing                             | 5m / reel (bag)  |       |



MW LIGHTING

UQS-COB-8W-W-24V




4

kWh/1000h



2019/2015

## MECHANICAL SPECIFICATION:



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Bars and Strips](#) category:*

*Click to view products by [POS manufacturer](#):*

Other Similar products are found below :

[LFBLL-SW823-24V-8S125-20](#) [LFBHL-SW927-24V-8S63-20](#) [RF-G30HI3510-241202081-A0 IP20](#) [RF-GW2H39W19-2406020I1-A1 IP20](#)  
[HH-SX144F008W24 -2835 WW WHITE PCB IP20](#) [N004120BB1LZ \(6000K\)](#) [N004120BC1LZ \(3000K\)](#) [N008120BB1LZ \(BLUE\)](#)  
[N008120BC1LZ \(4000K\)](#) [S008144CA4SA1/C1 \(RGB+4000K IP20\)](#) [S0121134ZC3PZ](#) [COB-480-CW-24-10W](#) [HQS-14.4W-60LED-RGB-](#)  
[WP-12V-5M](#) [N013060CA3SA1](#) [HQS-12W-60LED-W-WP-24V-5M](#) [UQS-COB-12W-NW-24V-5M](#) [HH-SNW480F208W24-COB-R](#) [HQS-](#)  
[12W-60LED-NW-WP-12V-5M](#) [S012120BC1HZ \(WARM WHITE\)](#) [HQS-6W-60LED-WW-WP-24V-5M](#) [COB-480-NW-24-10W](#)  
[S020240BC1DC0/C3](#) [S012060CB4SA1/C2](#) [HQS-12W-60LED-WW-WP-24V-5M](#) [HH-SW480F008W24-COB-R](#) [HH-SWW320F008W24-](#)  
[COB-R](#) [COB-480-WW-24-10W](#) [HQS-6W-60LED-NW-WP-12V-5M](#) [S012060CC4DC0/C3](#) [HH-SWW320F208W12-COB-R](#) [S012048CB4PZ](#)  
[\(RGB+W:3000K\)](#) [HQS-9.6W-120LED-NW-WP-12V-5M](#) [S012480ZB1SF \(WARM WHITE IP20\)](#) [HQS-6W-60LED-WW-12V-5M](#)  
[S012120BC1HZ \(COLD WHITE\)](#) [HQS-6W-60LED-W-WP-12V-5M](#) [HQS-6W-60LED-W-12V-5M](#) [HQS-9.6W-120LED-NW-24V-5M](#) [HQS-](#)  
[9.6W-120LED-NW-12V-5M](#) [HQS-12W-60LED-WW-12V-5M](#) [S012480ZB1SF \(COLD WHITE IP20\)](#) [HH-SRGB60F310W12-5050 WHITE](#)  
[PCB IP65A](#) [S010120BC3SM/C1](#) [UQS-COB-12W-W-24V-5M](#) [HQS-6W-60LED-NW-12V-5M](#) [HH-SW60F008W12-3528 CW WHITE PCB](#)  
[IP20](#) [HQS-6W-60LED-NW-24V-5M](#) [S004060BB3PZ/C2](#) [TAMA LED K2-30-1920-24V 19,2W/M](#) [TAMA LED K-30-2400-24V 24W/M](#)