

We've Got The Power.™

Sealed Nickel Cadmium Batteries

Model: PS-C

0°C

20°C

40°C


16

18

Specifications

Nominal Voltage		1.2 Volt
Rated Capacity		2000 mAh
Dimensions	Diameter in. (mm)	1.00 (25.3)
	Height in. (mm)	1.93 (49.0)
	Height with solder tabs	1.97 (50.0)
	Weight Approx.	68 gm
	Internal Resistance	< 20 mΩ
	Standard Charge (0.1C)	200 mA
	Trickle Charge	(0.03C)~(0.05C)
	Fast Charge ∆V	600 mA
Recommended	Std/Trickle Charge	20±5°C
Operating	Fast Charge	20±5°C
Temperature	Discharge	20±5°C
Range	Storage	-20°C to 45°C
Standard Discharge (0.2C) Cut Off Voltage		1.0V per cell
High Rate Discharge (1 C) Cut Off Voltage		1.0V per cell

Dimensions



Charging and Discharging Characteristics

1.60

1.55

1.50

1.45

1.25 1.20

1.15

1.10


0

2


4

6

(A) 1.40 1.35 1.30 1.25







Standard Charge

Time (min.)


8

10

Charging: 0.1C x 15 hrs.

12

14




Fast Charge

Trickle Charge



Model: PS-C



Corporate Headquarters and Domestic Sales

Power-Sonic Corporation • 7550 Panasonic Way • San Diego, CA 92154 •U.S.A Phone: (619) 661-2020 • Fax: (619) 661.3650 Email Sales: national-sales@power-sonic.com Email Customer Service: customer-service @power-sonic.com E-mail Technical Support: technical-support@power-sonic.com

International Sales

Power-Sonic Corporation • P.O. Box 5242 • Redwood City, CA 94063 • U.S.A. Phone: (650) 364-5001 • Fax: (650) 366-3662 Email Sales: international-sales.com@power-sonic.com

www.power-sonic.com

© Copyright 2010 Power-Sonic Corporation. All rights reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NiCd - Nickel Cadmium Battery category:

Click to view products by Power-Sonic manufacturer:

Other Similar products are found below :

PS-850AA-T PS-D-T PS-F PS-C-T PS-CX-T PS-C PS-AAX PS-850AA PS-1/2D 15568-1 PS-2/3AA PS-AA PS-AA PS-SC PS-AAX-T PS-1/2D-T KR1800SCE PS-2/3A PS-AAA PS-D