1	, 2		3 1		1 3	1	0			8	- I	9	ii - 1	0	11	- 1	12	<u></u>	13 1	14	
8	MOLDING TO	DL															REVIS	SION			
	MOLD OUTS	and and an end of the second se											Ī	REV.		DESCR	RIPTION		APPROVA	L DAT	TE
0041/	/0044 004	47/0048	C5- C4-	DETA	AIL A	+	30.5±0.	5			~	-6	Ī	А		NEW R	ELEASE		CUI MANMA	N 10.09	9.0
			C3 24 1 NL B 17		40.5±0.5				→ () → 34.5±0.5 →	1- 5-	O Ref	15 10	2 EAT SE	- 41		P1 C1 — C2 — C3 — 15 —	WIRE LIS	ST:	P2 - 1 - 2 - 3 - 5		
)					15.5±0.5			- SOVE		AL		C5— 14 — 16 —			10 6 7 8 9		
		<u>ETAIL A</u>	DETAIL E				12.	0±0.5	1PCS/F	PE BAG	6(0.06r	∃_ ! nm) F	ACKIN	G		/ — C4 — 8 — 6 —			- 12 - 13 - 14 - 15		
a		C Q	13.8 PowerSy 字稿:2.000 字体:Arial 移印雕色: cool;	ync _{gray 40}			12.	0±0.5						G	SF	/ — C4 — 8 — 6 — IELL —			- 14		
	PE BAG	PE BAG:60	13.8 PowerS 字斎:2.00 字体:Arial 穆印耀色: cool *90*0.06mm	ync _{gray 40}			12.	0±0.5		1PCS	•	NOTES:	SINGL	E ELE	CTRIC		ER FOIL	AFTER	- 14 - 15	AND	
6	PE BAG PVC	PE BAG:60 MOLDED 45	13.8 PowerSy 学病:2.000 学体:Arial 移印概色: cool *90*0.06mm PVC BLACK	ync gray 40 (S001)				0±0.5		1PCS 1PCS	N	NOTES: 1.360° SPOT	SINGL	E ELE	CTRIC	COPPE			- 14 - 15 - SHELL R INNER /	AND	
6	PE BAG	PE BAG:60 MOLDED 45 SCREW #4	13.8 PowerSy 学商:2.000 字体:Arial 移印颜色: cool, *90*0.06mm PVC BLACK -40UNC,L=¢	ync gray 40 n (S001) \$5.8*23m			SH _	<u>0±0.5</u>		1PCS	N	NOTES: 1.360° SPOT	SINGL	E ELE	CTRIC	COPPE			- 14 - 15 - SHELL	AND	-
6	PE BAG PVC	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU	13.8 PowerSy 学病:2.000 学体:Arial 移印概色: cool *90*0.06mm PVC BLACK	ync gray 4C n (S001) Ø5.8*23m INECTOR E(2935C)	SOLDE	R TYPE	SH CONTAC	O±0.5 CT GOLD		1PCS 1PCS	2	NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT	SINGL SOLDI MATERI TRONI 5 OPE FACT F	E ELE ER MC ALS/F C TES N SH RESIS	CTRIC DLDING ROCES ST CO ORT & TANCE	COPPE SES A NDITIC & MIS ¹ :1Ω/1	RE ROHS DN: WIRE TE MAX	S CON	- 14 - 15 - SHELL R INNER /		
6 5 4	PE BAG PVC SCREW	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU BACK SHE DVI 24+5	13.8 PowerSy 学術:Arial 非印度色: cool *90*0.06mm PVC BLACK -40UNC,L=¢ FEMALE CON JLATOR BLUE L TIN PLATE MALE CONN	ync aray 40 (S001) \$5.8*23m INECTOR E(2935C) ED ECTOR S	SOLDE).FRONT SOLDER	R TYPE SHELL TYPE C	CONTACT	<u>O±O.5</u> CT GOLD FLASH GOLD FI	ASH	1PCS 1PCS 2PCS		NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT INSU	SINGL SOLDI MATERI TRONI SOPE FACT F LATION	E ELE ER MC ALS/F C TES N SH RESIS	CTRIC DIDING PROCES ST CO ORT & TANCE SISTAN	COPPE SES A NDITIC & MIS ¹ :1Ω/1	RE ROHS DN: WIRE TE MAX	S CON	- 14 - 15 - SHELL R INNER /		
6 5 4 3	PE BAG PVC SCREW CONN.	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU BACK SHEI DVI 24+5 INSULATOR	13.8 PowerSy 学病:2.000 学体:Arial 非印度色: cool *90*0.06mm PVC BLACK -40UNC,L=@ FEMALE CON JLATOR BLUE LL TIN PLATE MALE CONNI BLACK.FRONT	ync sray 40 (S001) \$5.8*23m INECTOR E(2935C) ED ECTOR S SHELL G	SOLDE SOLDER	R TYPE SHELL TYPE C ASH BAC	CONTACT	O±O.5 CT GOLD FLASH GOLD FL - TIN PLAT	ASH	1PCS 1PCS 2PCS 1PCS		NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT INSU	SINGL SOLDI MATERI TRONI SOPE ACT F LATION mm	E ELE ER MC ALS/F C TES N SH RESIS N RES N RES D TITLE	CTRIC DLDING PROCES ST CO ORT & TANCE SISTANG	COPPE SES A NDITIC MIS ^V :1Ω/I CE:10	RE ROHS DN: WIRE TE MAX MΩ/MIN	S CON	- 14 - 15 - SHELL R INNER /		
6 5 4 3	PE BAG PVC SCREW CONN.	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU BACK SHEI DVI 24+5 INSULATOR HOOK UP	13.8 PowerSy 学術:Arial 非印度色: cool *90*0.06mm PVC BLACK -40UNC,L=¢ FEMALE CON JLATOR BLUE L TIN PLATE MALE CONN	ync sray 40 (S001) \$5.8*23m NECTOR E(2935C) ED ECTOR S SHELL G 1 28AWG ²	SOLDER SOLDER SOLD FL/ *1C TIN	R TYPE SHELL TYPE C ASH BAC	GOLD F CONTACT CONTACT CK SHELL	O±O.5 CT GOLD FLASH GOLD FL TIN PLAT WIRE,	ASH	1PCS 1PCS 2PCS 1PCS		NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT INSU SCALE SHEET DIMENSIONAL	SINGL SOLDI MATERI TRONI OPE ACT F LATION MONE 1/1 TOLERANCES	E ELE ER MC ALS/F C TES N SH RESIS N RES N RES DV 15 CUS.	CTRIC DLDING PROCES ST CO ORT & TANCE SISTANG	COPPE SES A NDITIC MIS ^V :1Ω/I CE:10	RE ROHS DN: WIRE TE MAX MΩ/MIN	S CON	- 14 - 15 - SHELL R INNER /		
④③②	PE BAG PVC SCREW CONN. CONN.	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU BACK SHEI DVI 24+5 INSULATOR HOOK UP INSULATION	13.8 PowerSy ?#3:2.000 ?#4:Arial #80006; cool PVC BLACK -40UNC,L=¢ FEMALE CON JLATOR BLUE L TIN PLATE MALE CONNI BLACK.FRONT WIRE:UL1061	ync gray 40 (S001) Ø5.8*23m INECTOR E(2935C) ED ECTOR S SHELL G 1 28AWG ² /C OD=0.	SOLDER SOLDER SOLD FL/ *1C TIN .9±0.1r	R TYPE SHELL TYPE C ASH BAC INED CC mm.L=2	GONTACT GOLD F CONTACT CONTACT COPPER N 22±1mm	O±0.5 CT GOLD FLASH GOLD FL TIN PLAT WIRE, 1.	ASH	1PCS 2PCS 1PCS 1PCS 7PCS		NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT INSU SCALE SHEET DIMENSIONAL	SINGL SOLDI MATERI TRONI OPE ACT F LATION MM NONE 1/1	E ELE ER MC ALS/F C TES N SH RESIS N RES N RES DV 15 CUS.	CTRIC DLDING PROCES ST CO ORT & TANCE SISTANG 24+5 ADAP P/N	COPPE SES A NDITIC MIS ^V :1Ω/I CE:10	RE ROHS DN: WIRE TE MAX MΩ/MIN HDD	S CON	- 14 - 15 - SHELL MPLIANT. DC 300		
6	PE BAG PVC SCREW CONN. CONN.	PE BAG:60 MOLDED 45 SCREW #4 HDD 15P FLASH.INSU BACK SHEI DVI 24+5 INSULATOR HOOK UP INSULATION HOOK UP	13.8 PowerSy 学样:Arial 移卵應色, cool *90*0.06mm PVC BLACK -40UNC,L=¢ FEMALE CON JLATOR BLUE LL TIN PLATE MALE CONNI BLACK.FRONT WIRE:UL1061	ync sray 40 (S001) \$5.8*23m NECTOR E(2935C) ED ECTOR S SHELL G 1 28AWG ² /C OD=0. 1 28AWG ²	SOLDER).FRONT SOLDER SOLD FL/ *1C TIN .9±0.1r *1C TIN	R TYPE SHELL TYPE C ASH BAC INED CC mm.L=2	GONTACT CONTACT CK SHELL OPPER V 22±1mm OPPER V	O±O.5 CT GOLD FLASH GOLD FL TIN PLAT WIRE, 1. WIRE,	ASH	1PCS 1PCS 2PCS 1PCS 1PCS		NOTES: 1.360° SPOT 2.ALL ELEC 100% CONT INSU	SINGL SOLDI MATERI TRONI OPE ACT F LATION MONE 1/1 TOLERNATES	E ELE ER MC ALS/F C TES N SH RESIS N RES N RES DV 15 CUS.	CTRIC DLDING PROCES ST CO ORT & TANCE SISTANG SISTANG 24+5 F ADAP P/N SCP	COPPE SES AI NDITIC & MIS ¹ :1Ω/I CE:10 M TO TER	RE ROHS DN: WIRE TE MAX MΩ/MIN HDD	S COM	- 14 - 15 - SHELL MPLIANT. DC 300	/	

文件編號:WI-GC-411-A/0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular DIN Connectors category:

Click to view products by PowerSync manufacturer:

Other Similar products are found below :

M83723/76W22326 M83723/78R22327 D38999/26FE99SN L/C 75-069228-21J 7519021610P 75-190224-28S 75-474014-07L 803000A09M040 FGG.1K.314.CLAK75 FRCIR030FP-28-21S FRCIR030RFP-40A-38P-F80 FRCIR06F-40A-38S-F80 FRCIR06R-14S-6S 88-569723-03P 88-569735-06P 88-569769-19P 88-569785-06I 8R3006A18M0033 GTC00G-24-7S PT05A-14-18SW(023) PT05A-14-5SX PT05A1832SW PT05A2041SX GTC030-20-27PW-LC GTC030A-20-33S GTC06R20-22P-025-LC 1211290078 1211810025 ACC06AF-20-23P(003) 1210503216 1211290084 ACS06AF-16-10P(003) D38999/40FB35AN D38999/40FB35BB D38999/40WB35BN D38999/40WD35PN D38999/40WJ29SN-L/C D38999/40WJ4BN D38999/42FB35BN D38999/42WB35AB D38999/42WB35PB-L/C D38999/42WJ19AN D38999/44WH21AN D38999/44WH35AN D38999/44WJ29BA D38999/44WJ35PN D38999/44WJ61BA D38999/46WF32PN-L/C D38999/46WF32PN(LESS CONT 12DL6MX