


FEATURES

- Resistances from 0.001Ohm to 100Ohms
- Power Rating to 50Watt
- Resistance Tolerances to $\pm 0.1\%$
- TCR to $\pm 10\text{ppm/K}$
- Very Low Inductance
- Load Stability to 0.1%



Pb-free
Available
RoHS*
COMPLIANT

TABLE 1 – SPECIFICATIONS		
TYPE		FHR 4-3825 FHR 4-3825H FHR 4-4618
Resistance Range		0.001 to 100 Ohms
Power Rating	Free air 70°C	3W / 5W for 3825H
	With heatsink	50W
Tolerances from 0R001		0.1% / 0.25% / 0.5% / 1% / 2% / 5%
Thermal Resistance		1.6 K/W
Stability (1000h)		0.1% / 0.2% / 0.5% (depends on stress)
Temperature Coefficient Standard (Q) Option (R) Extended Temperature Range		$\pm 25\text{ppm/K}$ (20 to 60°C) $\pm 50\text{ppm/K}$ (-40 to 130°C) other specifications upon request
Voltage Proof		500 VDC
Maximum Current		150 A / 200 A for contact F
Thermal EMF		< 1 $\mu\text{V/K}$
Operating Temperature Range		-40 to 130 °C
Resistor Material		CuNiMn-Foil
Substrate		Anodized aluminium
Housing		Epoxy
Connector Material		Cu / tinned
Terminals		4
Max. Torque		1 Nm

ORDERING INFORMATION
Part Number - Resistance - Contact - Tolerance - TCR
FHR 4-4618 0R050 F 1% Q
FHR 4-3825H 1R140 A 0.1% N

FIGURE 1 – TEMPERATURE COEFFICIENT





FIGURE 2 – DERATING




Power Rating Notes -

The FHR Series Resistors must be attached to a suitable heat-sink. The maximum internal resistor temperature is 130°C. To specify an appropriate heatsink use the following formula :

$$R_{0H} = \frac{T_{MAX} - (P \times R_{0R}) - T_A}{P}$$

Where: R_{0H} = Thermal Resistance of Heatsink (K/W)
 R_{0R} = Thermal Resistance of Resistor (K/W)
 T_{MAX} = Maximum Temperature of Resistor
 T_A = Ambient Temperature of Heatsink (°C)
 P = Power Through Resistor (W)


FIGURE 3 – DIMENSIONS in mm (inches)



Dimension		A-contact	K-contact
A ±0.2 (±0.008)		24.00 (0.94)	
B ±0.3 (±0.012)		38.00 (1.50)	
C ±0.1 (±0.004)		1.40 (0.06)	
D ±0.1 (±0.004)		4.00 (0.16)	
E ±0.2 (±0.008)		17.50 (0.69)	
F ±0.1 (±0.004)		1.5x45° (0.06x45°)	
G ±0.2 (±0.008)		27.50 (1.08)	
H ±0.2 (±0.008)		17.50 (0.69)	
I ±0.1 (±0.004)		1.50 (0.06)	1.10 (0.04)
J ±0.1 (±0.004)		3.00 (0.12)	
K ±0.1 (±0.004)		3.20 (0.13)	
L ±0.1 (±0.004)		2.00 (0.08)	
M ±0.2 (±0.008)	Standard	6.00 (0.24)	
M ±0.2 (±0.008)	Variant H	10.80 (0.43)	
N ±0.4 (±0.016)		30.40 (1.20)	
O ±0.2 (±0.008)		15.00 (0.59)	
P ±0.3 (±0.012)	R > 0R001	3.60 (0.14)	3.30 (0.13)
	R ≤ 0R001	4.10 (0.16)	----
Q ±0.3 (±0.012)	R > 0R001	2.80 (0.11)	
	R ≤ 0R001	3.30 (0.13)	
R ±0.2 (±0.008)		19.00 (0.75)	


FIGURE 3—DIMENSIONS in mm (inches)

FHR 4-3825 F-contact



Dimension	
A ±0.2 (±0.008)	24.00 (0.94)
B ±0.3 (±0.012)	38.00 (1.50)
C ±0.2 (±0.008)	1.50 (0.06)
D ±0.1 (±0.004)	4.00 (0.16)
E ±0.3 (±0.012)	34.00 (1.34)
F ±0.2 (±0.008)	17.50 (0.69)
G ±0.1 (±0.004)	1.5x45° (0.06x45°)
H ±0.2 (±0.008)	34.00 (1.34)
I ±0.2 (±0.008)	32.70 (1.29)
J ±0.2 (±0.008)	7.50 (0.30)
K ±0.2 (±0.008)	24.00 (0.94)
L ±0.2 (±0.008)	6.30 (0.25)
M ±0.1 (±0.004)	4.80 (0.19)
N ±0.1 (±0.004)	3.20 (0.13)
O ±0.1 (±0.004)	2.00 (0.08)
P ±0.2 (±0.008)	6.00 (0.24)
Q ±0.2 (±0.008)	15.00 (0.59)
R ±0.7 (±0.028)	4.10 (0.16)
S ±0.7 (±0.028)	3.30 (0.13)

FHR 4-4618



Dimension	A-contact	K-contact
A ±0.1 (±0.004)	17.00 (0.67)	
B ±0.3 (±0.012)	46.00 (1.81)	
C ±0.4 (±0.016)	1.40 (0.06)	
D ±0.2 (±0.008)	8.50 (0.33)	
E ±0.3 (±0.012)	40.00 (1.57)	
F ±0.3 (±0.012)	34.00 (1.34)	
G ±0.1 (±0.004)	1.5x45° (0.06x45°)	
H ±0.2 (±0.008)	17.50 (0.69)	
I ±0.2 (±0.008)	27.50 (1.08)	
J ±0.1 (±0.004)	1.50 (0.06)	1.10 (0.04)
K ±0.1 (±0.004)	3.00 (0.12)	
L ±0.1 (±0.004)	3.20 (0.13)	
M ±0.1 (±0.004)	2.00 (0.08)	
N ±0.2 (±0.008)	max.5.5 (0.22)	
O ±0.4 (±0.016)	23.40 (0.92)	
P ±0.2 (±0.008)	15.00 (0.59)	
Q ±0.3 (±0.012)	3.60 (0.14)	3.30 (0.13)
R ±0.3 (±0.012)	2.80 (0.11)	



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Powertron](#) manufacturer:

Other Similar products are found below :

[USR 4-4020 0R100 D 1%](#) [FPR 4-T227 0R100 G 1% Q](#) [FPR 2-T218 2R000 C 1%](#) [NPS 2-T126B 10R00 S 1%](#) [KHR 2-T227 10K00 G 1%](#)
[SHR 4-2321 0R005 S 1% M](#) [NPS 2-T126B 47R00 S 1%](#) [SPS 4-T220 0R100 S 1% M](#) [FPR 4-T227 0R010 G 1% Q](#) [FPS 4-T220 0R500 S 1% Q](#)
[FPR 2-T218 3R000 C 1%](#) [SHR 4-3825 0R010 A 1% M](#) [USR 2-T220B 500R0 S 0.1%](#) [KHR 2-T227 100R0 G 1%](#) [USR 4-4020 1R000 D 1%](#)
[USR 2-T220B 50R00 S 0.1%](#) [PCS 301 0R100 S 1%](#) [FPS 4-T220 0R005 S 1% Q](#) [FHR 4-2321 0R001 S 1% Q](#) [FHR 4-2321 0R005 S 1% Q](#)
[FPR 4-T221 0R220 S 1% Q](#) [SHR 4-3825 0R100 A 1% M](#) [FHR 4-3825 0R001 A 1% Q](#) [FPR 2-T218 4R000 C 1%](#) [FPR 4-T227 0R001 G 1% Q](#)
[KHR 2-T227 10R00 G 1%](#) [FPS 4-T220 0R010 S 1% Q](#) [SPR 4-T220 0R100 S 1% M](#) [FHR 4-3825 0R010 A 1% Q](#) [FHR 4-2321 0R010 S 1% Q](#)
[NPS 2-T126B 50R00 S 1%](#)