

MECHANICAL

Durability 40'000 cycles minimum
 Theoretical stroke S= 1.4 mm
 Recommended working level H= 6.15 to 7.3 mm
 Spring forces F1= 0.25 N initial (indicative value)
 F2= 0.85 N ±0.15 N at H= 6.8 mm
 Forces are measured in decompression mode


ELECTRICAL (TYPICAL VALUE)

Current per contact : max continuously 2 A
 max peak 3 A
 Contact resistance : 25 mOhm in static mode within recommended working height after full life

ENVIRONMENTAL

Operating temperature -25°C / +85°C
 Storage temperature -40°C / +85°C
 Relative humidity 5% / 95%

Pos.	Désignation	Qté	Matière - Protection
3	Spring 0-99-00046-S0	1	Music wire DIN 17223 - 0.1µm Au / 2.5µm NiP
2	Piston 70072-S0	1	CuZn36Pb3 - 0.5µm Au / 2.5µm Ni
1	Barrel 80212-S0	1	CuZn36Pb3 - 0.25µm Au / max 2.5µm NiP ①

M. à jour le 16.02.11 (1014) R1 le 18.02.16 (6014)		04-204		Remplace:	
SPRING-LOADED CONTACT  precipip swiss world connects				Remplacé par:	
				20:1	
				Contrôlé	
				N° dessin	
				Révision	
				90156-AS	
				R1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Precidip](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)