


KRF 1025S



KRF-1025S is a crimping tool for right angeled uninsulated connectors, 1.0 - 2.5 mm²/AWG 18 - 14, B/F-Crimp.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability





Crimp profile

TECHNICAL DATA

Length: 204 mm/8.03" Width: 22 mm/0.87" Height: 76 mm/2.99" Weight: 560 gr/1.23 lb Wire size: 1-2.5 mm² / AWG 18-AWG 14 Crimp dimensions mm/mm²: 1,0 - 2,5 mm² Crimp dimensions inch/AWG: AWG 18 - 14 Connector: Uninsulated 90° angeled open barrel connectors Description: For uninsulated angeled open barrel cannoectors. Life span, cycles: 50,000

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Crimpers / Crimping Tools category:

Click to view products by Pressmaster manufacturer:

Other Similar products are found below :

010-0096 M225201-06 M225202-37 6-1579015-5 CT150-2-D02 CT150-6-RH07 622-6441LF M322 6-304052-1 63456-0054 63484-3701 63800-8355 63819-1875 63819-2875 63819-4475 63823-3475 63827-5375 64001-0975 64001-4175 64005-0175 662903-2 690602-6 7-1579001-9 7-23471-1 762637-1 808714-1 811242-5 91362-1 999-50-020083 1-21002-3 1-21002-7 12085270 1-21002-6 1-21113-6 1-22548-4 125442-1 DCE.91.073.BVC DCE.91.090.3MVM DCE.91.130.5MVU DCE.91.202.BVCM 1338300-1 1-354003-0 1338301-1 DF62/RE-MD 142321 AP105-DF11-24288(64) 1456088-1 1490794-1 1-45804-6 1490357-2