



**STP1100/ 1101 / 1102 / 1103**  
**Component Box**



Protecting parts from the damaging effects of Static Electricity.  
ESD containers are molded in conductive material for use in clean rooms and work stations.  
The ESD Materials are conform to ANSI/ESD S20.20 2007 requirements for ESD Packaging.  
This standard requires conductive material surface resistance to be 10 to 4-6 when tested  
by EOS/ESD S11.11. The materials also conform to the static decay requirement of FTM 101B  
Method 4046.1 dissipating a 5000 volt charges to 0 when grounded in less than 2 seconds.

<b>Material</b>	: Conductive
<b>Surface Resistivity</b>	: Conductive Materials 10 to 4 – 6.
<b>Test Method</b>	: ASTM D257 (ohms/square)
<b>Static Decay</b>	: < 2 seconds
<b>Test Method</b>	: FTM 101B
<b>Temperature Range</b>	: 40F to 225F
<b>HS Code</b>	: 3920300000
<b>Color</b>	: Black

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Antistatic Control Products](#) category:*

*Click to view products by [PRINTTEC](#) manufacturer:*

Other Similar products are found below :

[13020](#) [13490](#) [13881](#) [13883](#) [14404](#) [2202SP](#) [2229](#) [2230](#) [37061](#) [42470](#) [09813](#) [09857](#) [04563](#) [09037](#) [09813](#) [66070](#) [98132](#) [73741](#) [13868](#)  
[13457](#) [13245](#) [13420](#) [13205](#) [13135](#) [91070](#) [66085](#) [13080](#) [13806](#) [19863](#) [09121](#) [73831](#) [07501](#) [66086](#) [66121](#) [16316](#) [13331](#) [ZN-A2502](#) [ZJ-](#)  
[SD100](#) [1900-8X12](#) [1910-10X12](#) [82A3](#) [1900-6X8](#) [1900-7-15](#) [12917](#) [2231](#) [19866](#) [20-014-0002](#) [20-082-0010](#) [20-082-1012](#) [STS1327](#)