

STP1410 / STP1412 / STP1415 / STP1425
Conductive Copper Tape self adhesive



Material	: Conductive copper foil with a paper liner
Main Characteristic	: Thermosetting Conductive
Adhesive Type	: F(155°C)
Thermal Classification	: 0,035
Backing Thickness (mm)	: 0,06
Peel Strength (N/cm)	: 40
Tensile Strength (N/cm)	: 1 hour at 150°C or 2 hours at 130°C
Recommended curing cycle	: 0.003OHMS Tested in accordance with ASTM D-1000 Latest issue, VDE 0340, B.S.3924
Electrical resistance through adhesive*	: *Tested according to mil std 202F method 307 across surface area of 1 Sq.inch

All values shown are approximate and intended solely as a guide. No liability is accepted for their accuracy. It is the users responsibility to determine the suitability of the product for the intended application

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PRINTTEC](#) manufacturer:

Other Similar products are found below :

[ST250010](#) [ST250020](#) [ST250030](#) [ST250050](#) [STC1102](#) [STC1103](#) [STC1104](#) [STC1105](#) [STC1106](#) [STC1107](#) [STC1152](#) [STC1165](#) [STC1201](#)
[STC1202](#) [STC1203](#) [STC1204](#) [STC1205](#) [STC1206](#) [STC1207](#) [STC5101](#) [STC5102](#) [STC5103](#) [STC5104](#) [STC5201](#) [STC5202](#) [STC5203](#)
[STC5302](#) [STC5303](#) [STC5401](#) [STC5402](#) [STC5403](#) [STC5502](#) [STC5503](#) [STC5902](#) [STC5951](#) [STCL11104](#) [STCL11106](#) [STCL11109](#)
[STL1212](#) [STL1222](#) [STL1638](#) [STL2545](#) [STL3875](#) [STNBSF43](#) [STNBSF64](#) [STP10076127](#) [STP10102152](#) [STP10127203](#) [STP10152203](#)
[STP10152254](#)