

TYPE No	CORES	MIN	MAX	TYPE No	CORES	MIN	MAX	TYPE No	CORES	MIN	
7-2-2C	2	3.6	4.1	7-2-10C	10	6.3	6.9	7-2-25C	25	9.2	
7-2-3C	3	3.8	4.3	7-2-12C	12	6.6	7.2	7-2-36C	36	10.2	
7-2-4C	4	4.1	4.6	7-2-15C	15	7.4	8.0	7-2-50C	50	12.2	
7-2-6C	6	5.3	5.9	7-2-18C	18	7.9	8.5				
7-2-8C	8	5.7	6.3	7-2-20C	20	8.3	8.9				
37/0.315MM PVC INSULATED OVERALL BRAID SCREENED, PVC SHEATHED											
FILL FACTOR OF BRAID SCREEN 0.7.		0.2 MM		440 VOLTS ac r.m.s. at 1600hz		1.00 AMP		7/0.0076			
NOMINAL CONDUCTOR AREA (PER CORE)		MAX OPERATING TEMPERATURE		NOMINAL INSULATION RADIAL THICKNESS ON CORE		NOMINAL CONDUCTOR DIAMETER PER CORE		NOMINAL CORE RESISTANCE		NOMINAL CORE DIAMETER	
0.22 MM ²		70 °C		0.2MM		0.3 MM		20 °C 348 G/KM		1.2 MM	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [pro power manufacturer](#):

Other Similar products are found below :

[LTP-004-6036-BLK](#) [CPR400 CANISTER PACK 27/7/.1X2 50](#) [JY1244 BLK](#) [KS24N](#) [PVS-024-1100-BLK](#) [PV24 GROMMET PK 100](#)
[RB1804](#) [CTFC12-12](#) [PP7102](#) [PP14791](#) [PP001103](#) [PP001097](#) [PP001091](#) [PP001061](#) [PP001059](#) [PP000953](#) [PP000945](#) [PP001320](#) [PP000889](#)
[PP001225](#) [PP001175](#) [PP000649](#) [PP000501](#) [PP001060](#) [PP000486](#) [PP001054](#) [PP000420](#) [PP000389](#) [PP000364](#) [PP000284](#) [PP000283](#)
[PP000244](#) [PP000708](#) [PP000205](#) [PP000701](#) [PP000180](#) [PP000672](#) [PP000173](#) [PP000630](#) [PP000115](#) [PP000088](#) [PP000466](#) [PP000462](#)
[PP000024](#) [PP000277](#) [PP000135](#) [CTFCS150-18U](#) [PP000085](#) [PP000025](#)