

Fast Acting | 0.04x0.02 inch Thick Film Chip Fuses


0402FA Series



0402FA Series Chip fuses set the industry standard for performance, reliability and quality. The solder-free design provides excellent on-off and temperature cycling characteristics and also makes our chip fuses more heat and shock tolerant than typical subminiature fuses

Features

- Fast acting for excessive current
- Compatible with reflow and wave solder
- Ceramic and glass construction
- Excellent environmental integrity
- One time positive disconnect
- Lead Free and Halogen free materia



Applications

- Flat panel displays and televisions
- Automotive infotainment and ECU
- Computer servers
- Portable electronics
- Mobile device chargers

Electrical Characteristics

Amp Rating	% of Amp Rating	Opening Time
0.20~4A	100%	4 Hours Min.
1~4A	250%	5 Seconds Max.
0.20~0.75A	300%	5 Seconds Max.

Specifications

Part Number	Ampere Rating (A)	Voltage Rating (Vdc)	Interrupting Rating	Typical Cold Resistance (Ohms)	Typical Melting I ² t (A ² Sec)
0402FA-R200	0.200	32	32V@35A	2.250	0.0006
0402FA-R250	0.250	32	32V@35A	1.500	0.0010
0402FA-R315	0.315	32	32V@35A	1.000	0.0014
0402FA-R375	0.375	32	32V@35A	0.780	0.0018
0402FA-R500	0.500	32	32V@35A	0.500	0.0043
0402FA-R750	0.750	32	32V@35A	0.220	0.0110
0402FA-1A	1.00	32	32V@35A	0.130	0.0400
0402FA-1.25A	1.25	32	32V@35A	0.100	0.0480
0402FA-1.5A	1.50	32	32V@35A	0.078	0.0600
0402FA-2A	2.00	32	32V@35A	0.040	0.1300
0402FA-2.5A	2.50	32	32V@35A	0.024	0.2000
0402FA-3A	3.00	32	32V@35A	0.018	0.3300
0402FA-3.5A	3.50	32	32V@35A	0.014	0.4500
0402FA-4A	4.00	32	32V@35A	0.011	0.6000

- DC Interrupting Rating (Measured at rated voltage, time constant of less than 50 microseconds, battery source);
- DC Cold Resistance are measured at <10% of rated current in ambient temperature of 25 degrees;
- Typical Melting I²t (Measured with a battery bank at rated DC voltage, Measured at 1ms open time, time constant of calibrated circuit less than 50 microseconds).


Fast Acting | 0.04x0.02 inch

Thick Film Chip Fuses


0402FA Series

Dimension

Unit: mm/inch




Pad layout



Packaging

- Quantity: 10,000pcs
- 8mm wide tape on 178mm(7 inch) diameter reel -specification EIA Standard 481.

Soldering Parameters




Wave Soldering: 260°C, 10 seconds max.
Infrared Reflow: 260°C, 30 seconds max.

IR Reflow Profile

Preheat Heat	
Temperature min (T _{min})	150°C
Temperature max (T _{max})	200°C
Time (T _{min} to T _{max}) (ts)	60 - 120 seconds
Average ramp-up rate (T _{max} to T _p)	3°C/second max.
Liquidous temperature (T_L)	
Time at liquidous (t _L)	60 - 150 seconds
Peak temperature (T_p)	
Peak temperature (T _p)	260+0/-5°C
Time within 5°C of actual peak Temperature (t_p)	
Time within 5°C of actual peak Temperature (t _p)	10 - 30 seconds
Average ramp-down rate (T _p to T _{max})	6°C/second max.
Time 25 °C to peak temperature	8 minutes max.

Temperature Derating Curve




- Normal ambient temperature: 23+/-3°C
- Operating temperature: -55 ~ 150°C, with proper correction factor applied

Fast Acting | 0.04x0.02 inch

Thick Film Chip Fuses

0402FA Series

Average Time Current Curves



© 2021 PROSEMI Inc. All Rights Reserved.
 Specifications and features are subject to change without notice.
www.prosemitech.com

The PROSEMI logo, and all other PROSEMI trademarks are the property of PROSEMI Inc. All other trademarks are the property of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Surface Mount Fuses](#) category:

Click to view products by [PROSEMI](#) manufacturer:

Other Similar products are found below :

[FHC20402ADTP](#) [NFVC6125S0R50TRF](#) [SFT-125MA](#) [TF16SN2.00TTD](#) [FCC16501ABTP](#) [FCC16102ABTP](#) [FHC16322ADTP](#) [0308.250UR](#)
[0308.375UR](#) [0308.500UR](#) [0308.750UR](#) [0308001.UR](#) [030801.5UR](#) [F0603G0R03FNTR](#) [SKY87604-12](#) [SKY87604-11](#) [SKY87604-13](#)
[7010.9962.63](#) [R451003.L](#) [R451.500L](#) [R451001.L](#) [3-103-119](#) [3-103-123](#) [SGB401](#) [SGB075](#) [0154002.DRL](#) [0154008.DRL](#) [0154.500DRL](#)
[189140.1,25](#) [189140.0,8](#) [189140.0,4](#) [189140.0,63](#) [189140.0,25](#) [0402FA-R200](#) [0402SFF150F/24-2](#) [0435.250KRHFS](#) [0468003.WR](#)
[0494001.NRHF](#) [0494002.NRHF](#) [0494003.NRHF](#) [049402.5NRHF](#) [049403.5NRHF](#) [0494.250NRHF](#) [0494.375NRHF](#) [0494.500NRHF](#)
[CF06V3T1R60](#) [CF06V3T2R50](#) [06H1300D](#) [JFC0603-1200FS](#) [CP06V3T2R0](#)