

# USER MANUAL

## Table of Contents

<b>1.0 Introduction.....</b>	<b>1</b>
<b>2.0 Specifications.....</b>	<b>1</b>
<b>3.0 Package Contents.....</b>	<b>2</b>
<b>4.0 Panel Descriptions.....</b>	<b>2</b>
<b>5.0 Connection and Operation.....</b>	<b>2</b>

# USB3.0 Active Cable

## DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

## 1.0 INTRODUCTION

This is a USB3.0 Active Cable with a 5 m cable at the input side and a USB3.0 A type female port at the output side. It can extend the super speed signals up to 13 m max totally by connecting a 8 m high quality USB3.0 cable to the output port. It would be very convenient when you use devices which have USB3.0 port especially for long distance.

## 1.1 FEATURES

This USB3.0 Active Cable has many features that enable it to perform in a superior manner. Among those features you will find:

- Super speed USB3.0 supports 5Gbps data rate, over 10 times of USB2.0 Performance.
- Compatible with USB 3.0/2.0/1.1.
- Support the following speed data rate as follows: Low-speed (1.5Mbps)/ Full-speed (12Mbps)/High-speed (480Mbps) /Super-speed (5Gbps).
- Active USB extender cable ensures signal transmission stability.
- Hot plug capability.
- Extend single up to max 13 m.
- Support win2000/XP/Vista/win7/MAC OS.

## 2.0 SPECIFICATIONS

<b>Signal Inputs/Output</b>	
Input Signal	USB3.0
Output Signal	USB3.0
<b>Operating Frequency</b>	
Bandwidth	Max up to 5Gbps
<b>Warranty</b>	
Limited Warranty	1 Year Parts and Labor
<b>Environmental</b>	
Operating Temperature	0°C to +70°C
Operating Humidity	10% to 80 % RH (no condensation)
Storage Temperature	-10°C to +80°C
Storage Humidity	5% to 90 % RH (no condensation)
<b>Regulatory Approvals</b>	
Extender Unit	FCC,CE
<b>Accessories Adapter</b>	
User Manual	1 x English

# USB3.0 Active Cable


**Note:** Specifications are subject to change without notice. Weight and dimensions are approximate.

## 3.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- 1) Main unit.
- 2) User's Manual.

## 4.0 PANEL DESCRIPTIONS



- ① Device  
Connect this port to devices such as HDD, SSD, U disk, etc.
- ② Host  
Connect this port to PC/notebook/Ultrabook.

## 5.0 CONNECTION AND OPERATION

### 5.1 CONNECTION

- 1) Connect the “Host” side of USB3.0 Active Cable in to the USB3.0 port on PC or Ultrabook.
- 2) Connect the “Device” side of USB3.0 active cable to USB 3.0 device by one USB3.0 A type male to A type male or Micro USB female cable.

### 5.1 CONECTION DIAGRAM



P/N: 5017

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pro Signal](#) manufacturer:*

Other Similar products are found below :

[11.99.8795](#) [11.99.8871](#) [11W3-S6110-6IN](#) [1290B](#) [24-13485](#) [24-13486](#) [24-13545](#) [24-15620](#) [24-15621](#) [24-15622](#) [24-15623](#) [24-15624](#) [24-15625](#) [24-15626](#) [24-15627](#) [24-15628](#) [27-1450](#) [27-5915](#) [27-8076](#) [27-8174](#) [27-8192](#) [27-8355](#) [27-9576](#) [27-9579](#) [27-9650](#) [27-9656](#) [27-9662](#) [27-9750](#) [27-9756](#) [27-9760](#) [31000R](#) [31005R](#) [31040R](#) [33-12710](#) [35S2R-12](#) [50-14275](#) [50-14450](#) [50-14455](#) [50-14534](#) [50-14790](#) [50-14796](#) [52-125](#) [6410B](#) [83-12931](#) [83-12995](#) [83-12996](#) [83-12999](#) [83-16852](#) [83-16853](#) [83-17097](#)