



**FLEX-DOT screwdrivers. The allrounders for workshop and assembly.**



- ❶ Blade symbol and size on end of grip.
- ❷ With transverse hole for hanging up or applying a lever.
- ❸ Oil- and acid resistant non-stick special rubber handle.
- ❹ Finger recesses for more grip during fast turning.
- ❺ Easy-to-read sizes through laser marking process on matte-chrome plated shafts of chrome-silicon-manganesemolybdenum special alloy steel.
- ❻ Processed black tip for greatest precision for accepting screws. Also prevents tool from slipping.

## ***Ergonomic design for proper handling:***

Rounded two-component handle with flexible "FLEX-DOT®" nubs for fatigue-proof and comfortable continuous use. Excellent grip attitude also with quick regripping. Combines high torques and pressure forces with balanced design for horizontal and vertical approach.

**2 YEAR  
GUARANTEE!**

For full  
professional use!

**DIN  
ISO**

## Flat-blade screwdrivers



| NO     | mm   | mm  | mm  | mm  |     |
|--------|------|-----|-----|-----|-----|
| 22 010 | 3.0  | 0.5 | 100 | 75  | 1   |
| 22 012 | 4.0  | 0.8 | 100 | 75  | 1   |
| 22 014 | 5.5  | 1.0 | 125 | 100 | 1   |
| 22 016 | 6.5  | 1.2 | 150 | 110 | 2   |
| 22 018 | 8.0  | 1.2 | 175 | 122 | 2 3 |
| 22 020 | 10.0 | 1.6 | 200 | 122 | 2 3 |
| 22 026 | 5.5  | 1.0 | 25  | 60  | 1   |
| Stubby |      |     |     |     |     |



Matt-chrome plated blades of chrome vanadium special steel with precision black tip.



With hexagon flat for using an openend spanner as lever (for sizes 8 and 10 on slotted and PH3 and PZ3 version).

## PHILLIPS screwdrivers



| NO     | PH | mm  | mm  |   |
|--------|----|-----|-----|---|
| 22 050 | 0  | 60  | 75  |   |
| 22 052 | 1  | 80  | 100 |   |
| 22 054 | 2  | 100 | 110 |   |
| 22 056 | 3  | 150 | 122 | 3 |
| 22 060 | 2  | 25  | 60  |   |
| Stubby |    |     |     |   |

## POZIDRIV PHILLIPS screwdrivers



| NO     | PZ | mm  | mm  |
|--------|----|-----|-----|
| 22 070 | 0  | 60  | 75  |
| 22 072 | 1  | 80  | 100 |
| 22 074 | 2  | 100 | 110 |
| 22 076 | 3  | 150 | 122 |

3

## HX (ball-head) screwdrivers



| NO     | Innen HX | mm  | mm  |
|--------|----------|-----|-----|
| 22 204 | 2        | 100 | 75  |
| 22 206 | 2.5      | 100 | 75  |
| 22 208 | 3        | 100 | 75  |
| 22 210 | 4        | 100 | 100 |
| 22 212 | 5        | 100 | 110 |
| 22 214 | 6        | 150 | 110 |
| 22 216 | 8        | 150 | 122 |



Difficult to access Allen screws can be screwed at a working angle of up to 25° with HX Ball.

## TX Tamper screwdrivers

(with frontal hole)



| NO     | TTX | mm  | mm  |
|--------|-----|-----|-----|
| 22 230 | 8   | 75  | 75  |
| 22 232 | 10  | 100 | 100 |
| 22 234 | 15  | 100 | 100 |
| 22 236 | 20  | 100 | 100 |
| 22 238 | 25  | 100 | 110 |
| 22 240 | 27  | 100 | 110 |
| 22 242 | 30  | 100 | 110 |
| 22 244 | 40  | 100 | 110 |

## 1/4" quick-change bit screwdriver with spring sleeve

For standard 1/4" hex bits (6.35mm). The auto-lock-system positively holds the bit. To release, push the sleeve backwards.



| NO     | mm  | mm  |
|--------|-----|-----|
| 22 282 | 110 | 110 |

## HX nut screwdrivers



| NO     | Außen HX | mm  | mm  |
|--------|----------|-----|-----|
| 22 260 | 5.5      | 125 | 110 |
| 22 262 | 6        | 125 | 110 |
| 22 264 | 7        | 125 | 110 |
| 22 266 | 8        | 125 | 110 |
| 22 268 | 9        | 125 | 110 |
| 22 270 | 10       | 125 | 110 |
| 22 272 | 11       | 125 | 110 |
| 22 274 | 12       | 125 | 110 |
| 22 276 | 13       | 125 | 110 |



## Combination-Screwdriver with 1/4"-square and 1/4"-bit-holder

For use with 1/4"-square sockets or 1/4"-hexagon standard bits (6.3mm). Choice between the two options simply by sliding the sleeve.



| NO     | mm  | mm  |
|--------|-----|-----|
| 22 283 | 110 | 110 |



## 1/4" magnetic bit screwdriver

For 1/4" hexagon standard bits (6.35mm). Steel screws stick to magnetised bit which facilitates positioning of the screws.



mm  
100



mm  
110

NO  
22 281

## FLEX-DOT 6-piece screwdriver sets

Complete initial equipment for mechanics and service technicians.



|               |   |   |
|---------------|---|---|
| <b>NO</b>     |   |   |
| <b>22 604</b> | ● | 3.0 - 4.0 - 5.5 - 6.5                               |
|               | ⊕ | PH 1 - PH 2   |
| <b>22 606</b> | ● | 3.0 - 4.0 - 5.5 - 6.5                               |
|               | ✱ | PZ 1 - PZ 2   |
| <b>22 640</b> | ✱ | TTX 10 - TTX 15 - TTX 20 - TTX 25 - TTX 30 - TTX 40 |
| <b>22 642</b> | ○ | HX 2.5 - HX 3 - HX 4 - HX 5 - HX 6 - HX 8           |
| <b>22 644</b> | ● | External HX: 5.5 - 6 - 7 - 8 - 10 - 13              |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) category:*

*Click to view products by [Proxxon](#) manufacturer:*

Other Similar products are found below :

[1406504-2](#) [272012M](#) [271001M](#) [30246](#) [HMM-HH](#) [32024](#) [TL10416](#) [612020B](#) [35-045](#) [6951](#) [83](#) [9977](#) [EMF](#) [99833](#) [RB1](#) [S3166V](#) [X103V](#)  
[XTD10TP](#) [X108N](#) [HS7N](#) [HS618N](#) [LN25MMN](#) [HS18N](#) [XST1010N](#) [P4N](#) [R146N](#) [P12SN](#) [R5324N](#) [99764N](#) [P8N](#) [99312N](#) [R3163N](#)  
[SX101N](#) [LN22N](#) [XTD10N](#) [9955MMN](#) [995MMN](#) [996MMN](#) [LN25N](#) [THS9N](#) [R3166N](#) [R144N](#) [RB2N](#) [HS10N](#) [99964BPN](#) [HS11N](#) [HS12N](#)  
[THS8N](#) [TL12N](#) [LN23BPN](#)