

			_	
SPECIFICATIONS				
PARAMETERS	VALUES	UNITS		
DIRECTIVITY	OMNI	-		
SENSITIVTY	-46 ± 3	dB		
STANDARD OPERATING VOLTAGE	1.5	Vdc		
MAX OPERATING VOLTAGE	10	Vdc		
CURRENT CONSUMPTION (MAX)	0.5	mA		
IMPEDANCE	2.2	KOhm		
SIGNAL TO NOISE RATIO (MIN.)	>56	dB		
TERMINAL	SOLDER		1	
IERWIINAL	PAD			
INTERNAL CAPACITOR	N/A	pF		
	<u> </u>	<u> </u>	-	


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

REVISION HISTORY				
LTR	DESCRIPTION	DATE	APPROVED	
-	RELEASED FROM ENGINEERING	1/30/2006		
Α	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	9/13/2010	B.R.	
В	REVISED SIGNAL TO NOISE RATIO	2/14/2020	M.V.	







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE		Designed by	Date
SPECIFIED: DIMENSIONS ARE IN	SIZE	J.A.F.	1/31/20
MILLIMETERS,		∞	6 111
TOLERANCES ARE ±0.5 AND	A3		pui
ANGLES ARE ±3°.	, ,		
AOM-4546L-R.idw			a projects unli

So pul			AOM-4546L-R				
J.A.F.	1/31/2006	E.P.	1/31/2006	B.R.	1/31/2006	9/13/2010	
esigned by	Date	Checked by	Date	Approved by	Date	Drawn Date	

Microphone Edition Sheet 1 / 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by PUI Audio manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765
BCM9767P LD-MC-0905P LD-MC-6035 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T
CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035W LD-MC-9765P LD-MC9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T CMC-6027-42T GMI4522P-2C-30db
GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB
GMI4015P-36DB GMI4015P-46DB GMI4015P-54DB GMI4015P-58DB