

SPECIFICATIONS			
PARAMETERS	VALUES	UNITS	
DIRECTIVITY	OMNI	-	
SENSITIVTY	-44 ± 3	dB	
STANDARD OPERATING VOLTAGE	4.5	Vdc	
MAX OPERATING VOLTAGE	10	Vdc	
CURRENT CONSUMPTION (MAX)	0.5	mA	
IMPEDANCE	1	KOhm	
SIGNAL TO NOISE RATIO (MIN.)	60	dB	
TERMINAL	SOLDER PADS	-	
INTERNAL CAPACITOR	N/A	pF	


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. 1S PROHIBITED.

©2003, Projects Unlimited Inc.

REVISION HISTORY				
LTR	DESCRIPTION	DATE	APPROVED	
-	RELEASED FROM ENGINEERING	1/30/2006		
Α	ADDED TERMINAL POLARITY	1/30/2007	R.W.	
В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	9/16/2010	B.R.	







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:		Design
	SIZE	J.A
DIMENSIONS ARE IN MILLIMETERS,		\sim
TOLERANCES	Δ3	**
ARE ±0.5 AND ANGLES ARE ±3°.	<i>,</i> (0	X
AOM-5244	1L-R.idw	

J.A.F.	1/30/2006		٠.
	pui.		
	audic a projects unlimited co) Inc ompany	

Checked by	Date	Approved by	Date	Drawn Date	
E.P.	1/30/2006	B.R.	1/31/2006	9/16/2010	
AOM-5244L-R					

Microphone Edition Sheet

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by PUI Audio manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765
BCM9767P LD-MC-0905P LD-MC-6035 LD-MC-9765 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035P LD-MC-6035W LD-MC-9765P LD-MC-9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC-3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T CMC-6027-42T GMI4522P-2C-30db GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015P-36DB GMI4015P-46DB