SPECIFICATIONS			
PARAMETERS	VALUES	UNIT	
DIRECTIVITY	OMINI	-	
SENSITIVTY	-46 ± 3	dB	
STANDARD OPERATING VOLTAGE	2	Vdc	
MAX OPERATING VOLTAGE	10	Vdc	
CURRENT CONSUMPTION (MAX)	0.5	mA	
IMPEDANCE	2.2	KOhm	
SIGNAL TO NOISE RATIO (MIN.)	60	dB	
TERMINAL	PIN	-	
INTERNAL CAPACITOR	N/A	pF	

1. ALL DIMENSIONS ARE IN MILLIMETERS.

3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

WITHOUT NOTICE.

2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED. ©2003, Projects Unlimited Inc.

/ITHOUT PRIOR CTS UNLIMITED.	Ĺ
).	
d Inc	

REVISION HISTORY					
LTR	DESCRIPTION	DATE	APPROVED		
-	RELEASED FROM ENGINEERING	1/25/2006			
Α	ADDED TERMINAL POLARITY	2/2/2007	D.F.		
В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	9/27/2010	B.R.		

Checked by

Designed by

SIZE

Date

1/25/2006

Approved by

B.R.

Microphone

POM-2246P-2-R

Date

1/25/2006 9/27/2010


Drawn Date

Sheet

1/1

Date

1/25/2006



**UNLESS OTHERWISE** 

SPECIFIED:

DIMENSIONS ARE IN

MILLIMETERS,

TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.

POM-2246P-2-R.idw

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by PUI Audio manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765
BCM9767P LD-MC-0905P LD-MC-6035 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T
CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035W LD-MC-9765P LD-MC9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T CMC-6027-42T GMI4522P-2C-30db
GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB
GMI4015P-36DB GMI4015P-46DB GMI4015P-54DB GMI4015P-58DB