

SPECIFICATIONS						
PARAMETERS	VALUES	UNIT				
DIRECTIVITY	OMINI	-				
SENSITIVTY	-42 ± 3	dB				
STANDARD OPERATING VOLTAGE	2	Vdc				
MAX OPERATING VOLTAGE	10	Vdc				
CURRENT CONSUMPTION (MAX)	0.5	mA				
IMPEDANCE	2.2	KOhm				
SIGNAL TO NOISE RATIO (MIN.)	60	dB				
TERMINAL	SOLDER PADS	-				
INTERNAL CAPACITOR	N/A	pF				


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. LS PROHIBITED.

©2003, Projects Unlimited Inc.

-	REVISION HISTORY								
	LTR	DESCRIPTION	DATE	APPROVED					
1	-	RELEASED FROM ENGINEERING	1/25/2006						
	Α	ADDED TERMINAL TYPE AND POLARITY	2/5/2007	D.F.					
	В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/6/2010	B.R.					







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE		Designed by	Date	Checked by	Date	Approved by	Date	Drawn Date
SPECIFIED:	l SIZE	J.A.F.	1/25/2006	E.P.	1/25/2006	B.R.	1/25/2006	10/6/2010
DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND	A 3	3 pui.		POM-2742L-2-R				

1/1

POM-2742L-2-R.idw

ANGLES ARE ±3°.

Microphone

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by PUI Audio manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765
BCM9767P LD-MC-0905P LD-MC-6035 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T
CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035W LD-MC-9765P LD-MC9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T CMC-6027-42T GMI4522P-2C-30db
GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB
GMI4015P-36DB GMI4015P-46DB GMI4015P-54DB GMI4015P-58DB