

SPECIFICATIONS			
PARAMETERS	VALUES	UNIT	
DIRECTIVITY	UNI	-	
SENSITIVTY	-46 ± 4	dB	
STANDARD OPERATING VOLTAGE	2	Vdc	
MAX OPERATING VOLTAGE	10	Vdc	
CURRENT CONSUMPTION (MAX)	0.5	mA	
IMPEDANCE	2.2	KOhm	
SIGNAL TO NOISE RATIO (MIN.)	50	dB	
TERMINAL	SOLDER PADS	-	
INTERNAL CAPACITOR	-	рF	
CURRENT CONSUMPTION (MAX) IMPEDANCE SIGNAL TO NOISE RATIO (MIN.) TERMINAL	0.5 2.2 50	m/ KOh dE	


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003,	Projects	Unlimited	Inc

7	REVISION HISTORY			
	LTR	DESCRIPTION	DATE	APPROVED
	-	RELEASED FROM ENGINEERING	1/31/2006	
	Α	ADDED TERMINAL POLARITY	2/5/2007	D.F.
	В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/25/2010	B.R.
	С	REVISED SPECIFICATIONS AND TERMINALS	9/1/2011	M.L.
[D	REVISED SIGNAL TO NOISE RATIO	2/21/2020	M.V.







NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2011/65/EU COMPLIANT.

UNLESS OTHERWISE		Designed by	Date
SPECIFIED: DIMENSIONS ARE IN	SIZE	J.A.F.	1/31/20
MILLIMETERS,		(X)	6 1 II
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	A3		pul

•	1/31/2006	B.R.	1/31/20	006 10	0/25/2010
PUM-3046L-R					
		_		Edition	Sheet

Date

Drawn Date

1/1

Approved by

PUM-3046L-R.idw

Microphone

Checked by

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by PUI Audio manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765
BCM9767P LD-MC-0905P LD-MC-6035 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T
CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035W LD-MC-9765P LD-MC9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T CMC-6027-42T GMI4522P-2C-30db
GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB
GMI4015P-36DB GMI4015P-46DB GMI4015P-54DB GMI4015P-58DB