



RECOMMENDED PCB LAYOUT (Top View)
Tolerance: ±0.05

- Material:
1. Insulator: Glass-Reinforced Thermoplastic, UL 94V-0, Color: Black.
 2. Contact: Copper Alloy.
Contact Plating: Gold Plating on Contact Area.
Over Nickel underplating overall.
 3. ROHS Compliant
 4. Durability: 250 cycles min.
- Electrical:
1. Voltage Rating: 30 VAC.
 2. Current Rating: 0.5 A.
 3. Contact Resistance: 40 milliohms Max.
 4. Dielectric Withstanding Voltage: 500VAC Min.
 5. Insulation Resistance: 1000 Megaohms Min.
- Environmental:
1. Temperature Range: -40°C to +85°C.

PART NO.:	PART NUMBER	CONTACT	GOLD PLATING
	EB1M0-002-01-LT	20	15u''

DETACHED LISTS	MM (INCH)	RoHS Compliant		
	TOLERANCES EXCEPT AS NOTED	TITLE		
	.0 ± 0.2 ±	SFP CONNECTOR		SIZE
	.00 ± 0.15 ±	DFTO Peter	DRAWING NO. CE81M0-002-0X-LT	A3
	.000 ± 0.075 ±	DATE 07/10/2008	/PART NO. SEE TABLE	REV
	ANGLES ± 0.5	SCALE : 5:1	DO NOT SCALE DRAWING	2
	THIRD ANGLE PROJECTION		SHEET 1	OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [Pulse manufacturer](#):

Other Similar products are found below :

[571763P](#) [58098-0628](#) [72.250.1628.2](#) [72.250.2428.2](#) [74720-0505](#) [76.350.0729.0](#) [76871-1403](#) [FCN-244F080-G/1](#) [FCN-260A9920](#) [PCR-E36PM](#) [PCS-XE26MA+](#) [G38A71314B](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [172501-4002](#) [172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCR-E36FC+](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [U90B2054081210](#) [38113800006](#) [DP3AR020WQ1R200](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [500-1054](#) [ZP-4008-66L](#) [0709821002](#) [DX40-20P\(55\)](#) [5554841-1](#) [MS3474W18-8P-LC*](#) [SM3106F14S-7S-LC](#) [U90B3054061110](#) [U65-E04-4020](#) [ZPF00000000097891](#) [747360449](#) [10099439-003C-TRLF](#) [10137239-0021LF](#) [E9320-001-01](#) [10137239-0011LF](#) [70289-001LF](#) [70.060.1028.0](#)