

TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS



Features:

- 3-Feeds (4G, WiFi, GNSS)
- GNSS Active Antenna
 - LNA gain 30dB
 - Pre and post LNA filtering
- Direct mount
- Connector SMA Male
- Cable 17 feet
- RoHS compliant

Applications:

- 4G LTE 698-2700MHz
- WiFi dualband 2.4/5GHz
- DSRC 5850-5925GHz
- GNSS (Beidou, GPS, Galileo, Glonass)
- Vehicular mounting
- Asset Tracking, Navigation, Fleet Management
- Mobile and Fixed broadband

All dimensions are in mm / inches

Issue: 1709

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551

Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Frequency(LTE Cable)

Series: SharkFin

TECHNICAL DATA SHEET

MHz

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

698-960/1710-2170/2300-2700

ELECTRICAL SPECIFICATIONS

Frequency(WiFi cable)	2400-2485/5150-5925	MHz
	1561.098±2.046/	
Frequency(GNSS cable)	1575.42 ± 1.023	MHz
	1602.5625±4	
Nominal Impedance	50	Ω
VSWR (LTE)*	2.5:1	Max
VSWR (WiFi/GNSS)*	2:1	Max
Peak Gain (LTE,698-960MHz,Typical)**	3.0	dBi
Peak Gain (LTE,1710-2700MHz,Typical)**	4.5	dBi
Peak Gain (WiFi, 2400-2500MHz,Typical)**	4.1	dBi
Peak Gain (WiFi, 5150-5925MHz,Typical)**	5.9	dBi
Efficiency (LTE,698-960MHz,Typical)**	83	%
Efficiency (LTE,1710-2700MHz,Typical)**	82	%
Efficiency (WiFi,2400-2500MHz,Typical)**	82	%
Efficiency (WiFi,5150-5925MHz,Typical)**	54	%
HPBW / Horizontal Plane (LTE/WiFi)**	O	mni
HPBW / Vertical Plane (LTE, 698-960MHz, Typ	ical)** 52	2°
HPBW / Vertical Plane (LTE,1710-2700MHz, Ty	ypical)**	5°

Polarization (LTE/WiFi) Vertical Polarization (GNSS) **RHCP**

Power Withstanding (LTE, 698-960MHz) 100 W Power Withstanding (LTE, 1710-2700MHz) 20 W Power Withstanding (WiFi, 2400-5925MHz) 20 W

Issue: 1709



32°

25°

HPBW / Vertical Plane (WiFi, 2400-2485MHz, Typical)**

HPBW / Vertical Plane (WiFi,5150-5925MHz, Typical)**



TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

RHCP Peak Gain (Radiating element, Typical)*** 1 dBic	
Gain (LNA gain) $30 \text{ dB} \pm 2 \text{ dB}$	
Out of Band Rejection	
698 MHz >70 dB	
960MHz >65 dB	
1710MHz >60 dB	
2170MHz >65 dB	
2400MHz >65 dB	
2700MHz >65 dB	
Noise Figure <2.4 dB	
Operating Voltage 3.3-5 Vdc±0.5V	
Current Consumption 9 mA± 2 mA	



^{*} Tested with 5.18m cable and with 500mm ground plane

^{**}Tested with 200mm cable and with 500mm ground plane

^{***}Tested with 70X70mm ground plane



TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

MECHANICAL SPECIFICATIONS

Overall Length 3.5 H x Ø4.26 /88.3 x Ø108[in/mm]

Weight 470g

Antenna Color BLACK or WHITE

Connector type SMA MALE

Cable type RG58/RG174[GNSS/ LTE&WLAN]

Cable length 17' / 5.18m

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -40/+85 ° C

Storage Temperature -40/+85 ° C

Ingress Protection IP65

Wind-loading 120km/h

RoHS Compliant Yes






TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

MECHANICAL DRAWING









TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

Test Setup

* VSWR is tested with 5.18m cable and with 500mm ground plane

**Radiation performance is tested with 200mm cable and with 500mm ground plane

***GNSS module is tested with 70X70mm ground plane





TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

VSWR of LTE



VSWR of WiFi







TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

Radiation Efficiency of LTE



Radiation Efficiency of WiFi









TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

Peak Gain of LTE



Peak Gain of WiFi









TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

LTE antenna X-Y plane radiation pattern at LTE low band



LTE antenna Z-X plane radiation pattern at LTE low band







TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

LTE antenna Y-Z plane radiation pattern at LTE low band



LTE antenna X-Y plane radiation pattern at LTE high band







TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

LTE antenna Z-X plane radiation pattern at LTE high band



LTE antenna Y-Z plane radiation pattern at LTE high band



Issue: 1709

RoHS



TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

WiFi antenna X-Y plane radiation pattern at WiFi low band



WiFi antenna Z-X plane radiation pattern at WiFi low band







TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

WiFi antenna Y-Z plane radiation pattern at WiFi low band



WiFi antenna X-Y plane radiation pattern at WiFi high band







TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

WiFi antenna Z-X plane radiation pattern at WiFi high band



WiFi antenna Y-Z plane radiation pattern at WiFi high band



Issue: 1709

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

LNA Gain and out-of-band rejection



Radiation Pattern (70mm x 70mm ground plane) GPS & Galileo





TECHNICAL DATA SHEET


Description: 4G/WiFi/Active GNSS Direct

Mount Antenna


PART NUMBER: GNSSDM700/5800SSS

CHARTS

Radiation Pattern (70mm x 70mm ground plane) GLONASS



Radiation Pattern (70mm x 70mm ground plane) BD2







TECHNICAL DATA SHEET

Description: 4G/WiFi/Active GNSS Direct

Mount Antenna

PART NUMBER: GNSSDM700/5800SSS

PACKAGING

1pcs antennas per PE bag

12pcs antenna per package box

Package box: 400mm*300mm*30mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Pulse manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 W3006VP A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393