
TECHNICAL DATA SHEET



Series: Embedded Antenna


Description: On-ground BLE/NFC combo

PART NUMBER: W5101



Features:

- Own feed ports for 2.4GHz and NFC 13.56MHz
- Ultra thin 1.2mm
- Surface area 45x45mm
- Operates on top of metal ground plane
- Mounting with adhesive tape



Applications:

- Devices using 2.4GHz radios and 13.56MHz NFC connectivity
- BLE, Bluetooth, Zigbee, ISM 2.4GHz
- · Pairing, sharing

All dimensions are in mm / inches

Issue: 1613

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 12220 World Trade Drive San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 3611 NE 112th Ave Vancouver, WA 98682 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998





Series: Embedded Antenna

PART NUMBER: W5101

ELECTRICAL SPECIFICATIONS

Frequency P1	2400-2483.5 MHz
I ICAUCIICV I I	

Frequency P2 13.56 MHz

P1 nominal Impedance 50Ω

P1 VSWR <3:1

P1 Gain in free space 0.5dBi

P1 Gain over metal plate 1.5dBi

P2 Inductance in free space 1.13µH

P2 Q-value in free space 46

P2 Self Resonant Frequency in free space 57.6MHz

P2 Inductance over metal plate 1.11µH

P2 Q-value over metal plate 33

P2 Self Resonant Frequency over metal plate 53.8MHz

Connector type Contact pads



TECHNICAL DATA SHEET



Description: On-ground BLE/NFC combo

Series: Embedded Antenna

PART NUMBER: W5101

MECHANICAL SPECIFICATIONS

Color Black

Weight 5.7 g

Fixing system Pressure sensitive

adhesive

ENVIRONMENTAL SPECIFICATIONS

Operating temperature -40 to 85°C

Storage temperature MIL STD 810G: 24h at

85°C and 24h at -40°C

Temperature shock MIL STD 810G: Method

503.5, -40 for 1 hr to +85

C for 1 hr @ 15

deg.C/min rate of change;

3 cycles

Humidity MIL STD 810G: 24h at

60°C and 95%RH

Drop test Top, bottom, side. 3

times/orientation, 40"






Series: Embedded Antenna

PART NUMBER: W5101

MECHANICAL DRAWING







Series: Embedded Antenna

PART NUMBER: W5101

OTHER SPECIFICATIONS

Test setup over metal (80x80mm2). Material Ni plated steel Antenna contact points shown for BLE(P1) and NFC (P2)









Series: Embedded Antenna

PART NUMBER: W5101

CHARTS

P1










Series: Embedded Antenna

PART NUMBER: W5101


CHARTS

Vertical plane

P1



Horizontal plane









Series: Embedded Antenna

PART NUMBER: W5101

CHARTS



L @13.56MHz, µH	1.13
Q @13.56MHz	46
SRF, MHz	57.6



L @13.56MHz, μH	1.11
Q @13.56MHz	33
SRF, MHz	53.8

Issue: 1613



TECHNICAL DATA SHEET

Description: On-ground BLE/NFC combo

PART NUMBER: W5101

Series: Embedded Antenna

PACKAGING

Sealed plastic bag 60x90mm

ASSEMBLY

Pull off adhesive cover from backside and attach. Apply pressure 10N/cm² for 4 seconds to activate pressure sensitive adhesive.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by PulseLarsen manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352