

Qoltec Pure Sine Wave Inverter Monolith | 2000W | 4000W | 24V to 230V

Product code: 51939

The Qoltec inverter is a device that changes the 24 V direct voltage from the car installation to 230 V alternating voltage. It is ideal where there is no direct access to the power grid. The product has built-in mains sockets compatible with European plugs and a USB port.

PURE SINE WAVE INVERTER



Qoltec brand inverter is a pure sine wave, produces the same current as a 230V socket, ensuring safety for all connected devices. Great for both during power outages, as well as during travel when we do not have access to an outlet.

When choosing a suitable inverter, it is worth paying attention to the power value and voltage of the battery, which must be consistent with that indicated on the inverter to ensure that our equipment has the right conditions for work. Also important is the number of connected devices, for example, connecting a laptop and a printer, the power of both devices should be added up. Remember that the power consumed by the connected device should not exceed 85% of the rated power of the inverter.

COMPATIBLE WITH ANY TYPE OF POWER SUPPLY

WWW.QOLTEC.COM 1/5



The product is ideal as a power source in campers or trailers during family trips. Are you planning a longer camping or lakeside vacation and looking for a way to plug in your laptop or charge your phone on the yacht? It is worthwhile to be well prepared. With a Qoltec brand inverter, you will be able to power your devices anywhere and enjoy convenience and comfort. The voltage converter will be the ideal power source for yacht and boat owners. This smart device will allow you to power your equipment during long trips away from home, it has a USB port and power outlets to which you can plug electrical devices. Without any obstacles, you can charge your phone, laptop or plug in any other device whose power does not exceed the power of the inverter. Devices up to 150W such as a smartphone or a laptop while traveling can be powered by the energy drawn from the cigarette lighter socket. For equipment with higher power, we recommend using a battery with parameters compatible with the inverter.



 $\label{power consumed by the device} \textbf{Depending on the power consumed by the device}, the inverter can power:$

RTV equipment : TV, game console, music equipment, radio,

 $Household\ appliances: refrigerator, fridge, kettle, microwave, coffee \ maker, to a ster, to a ster \ oven,$

 $Of fice\ equipment: computers, printers, laptops,$

Other : power tools.

WWW.QOLTEC.COM 2 / 5





The case is designed from **high quality aluminum** that is resistant to **shock and mechanical damage**. It is an ideal choice for those who like to travel for long periods of time. Thanks to the inverter with built-in power socket, you can use almost any device that requires connection to the socket. The product has a **USB port** for charging mobile devices and a **fan** that takes care of proper cooling.

FULL GUARANTEE FOR SAFE USE



The product is equipped with a number of protections that guarantee full protection for connected devices. In addition, the kit includes a **spare fuse** to ensure the longest possible operation of the equipment.

The converter has: UVP protection - protects devices from too low voltage at the output, which affects the stability of connected devices, SCP protection - is a short circuit protection, OVP protection - is protection against too high output voltage and damage to connected devices, OCP protection - is protection against too high current on the line, OTP protection - is protection against overheating.

WWW.QOLTEC.COM 3 / 5

CONFIDENCE CONFIRMED BY A WARRANTY



Do you care about the high quality of the product you buy? Our solutions will meet your expectations. The product comes with a 24-month warranty valid from the date of purchase.

TECHNICAL DATA

WWW.QOLTEC.COM 4/5

Produce Oblice Rated Power 2000 W Peak passer 2500 W Output voltage 25 V Output voltage 25 V Usual frequency 9 H2 Value from 0.55 A Use gotter 5 SA Using system Fan Using system Fan Use port 5 V/2 X/OC 3.0 - 18W Protection 5 V/2 X/OC 3.0 - 18W Protection signature inverse posterity Fuse Protection signature inverse posterity Fuse Material All Inverse expressive labeling, computer, junited Other expressive labeling, computer, junited Collection signature inverse posterity Additional information 10°C + 20°C de 20°C Strange temperature - 10°C + 20°C de 20°C Additional information 20°C de 20°C de 20°C Expressions (D/Lx W x H) 20°C de 20°C de 20°C Expressions (D/Lx W x H) 20°C a 20°C de 20°C Package depth / Impt (Limit) 20°C a 20°C de 20°C Package depth / Impt (Limit) 20°C a 20°C de 20°C Package de		
Peak power 400W I second Input voltage 24 V Output voltage 230 V Output frequency 50 HZ Weedform 0.55 A Use current 0.55 A Efficiency 23 1 Coling system Fan USE port 5072A/OC 3.0 - 1880 Postaction UVP/OVP/OCPY/OTP/SCP Postaction against inverse polarity Fue Weet and Alkania Material Alkaninium Operating temperature -10°C - 150°C Storage temperature -10°C - 150°C Objecting temperature -10°C - 150°C Storage temperature -10°C - 150°C Addicional information 210 x 330 x 30 mm Package contents 1 x Newstern of Liver temperature Package contents 1 x Newstern of Liver temperature Alvanouring Keyn 1 x Newstern of Liver temperature Authority set 1 x Newstern of Liver temperature Package contents 1 x Newstern of Liver temperature A Fuel 1 x Newstern of Liver temperature	Producer	Qoltec
Input voltage 24 V Output victoge 250 V Output frequency 50 HZ Waveform 105 A Efficiency 25 A Coding system Fan Protection 50 MZA (0.5.0 – 18%) Protection 50 WZA (0.5.0 – 18%) Protection 50 WZA (0.5.0 – 18%) Protection 50 WZA (0.5.0 – 18%) Protection against inverse polarity Fus Material Adaminiman in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase polarity in Control (1.5 mail or part and in Fraging, Increase pola	Rated Power	2000 W
Output frequency 280 V Output frequency 90 H2 Vaverform Pure sine wave Ide current 0.55 A Efficiency 92 % Cooling system Fan USB part 8V2.20 (03.0 - 18W) Protection WVP/OVP/OCP/OCP/OTP/SCP Protection against inverse polarity Fix Beg Kitchen equipment findge, microwave, blender, coffee machine, lettle, freezer, oven Office equipment laptop, computer, printer Oberacid Aluminium Moteral Aluminium Operating temperature -10°C - 480°C Additional information Do not cover the verolitation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! so for a fair function of	Peak power	4000 W (5 second)
Output frequency 50 HZ Waveform Pore sine wave Icle current .0.55 A Efficiency 92 % Cooling system Fan USB port SVZA (QC 30 ~ 18M) Protection UVP/OVP/OVP/OTP/SCP Protection against inverse polanity Fuse Usage Ricchen equipment fridge, microwave, blender, coffer machine, kettle, freezer, owen Office equipment Liptop, computer, printer Other, power tools, nower, hair dryer, fan, IV, games console, radio, music equipment, solar panels, boat officiency of the power supply and consoler, radio, music equipment, solar panels, boat officiency of the power supply and panels, boat officiency of the power supply working correctly in Soft start function Operating temperature -10°C -+50°C Storage temperature -20°C do -20°C Additional information 20°C do -20°C Dimensions (O/L x W x H) 21 x New remember to connect the west later bases of the device Remember to connect the west and polarity of the power supply voltage correctly in Soft start function Package pontents 1 x New remember to connect the west and polarity of the power supply voltage correctly in X Name you will be a fact that the power supply voltage correctly in X Name you will be a fact that the power supply voltage correctly in X Name you will be a fact that the power supply voltage correctly in X Name you will be a fact that the power supply volta	Input voltage	24 V
Waveform Pure sine wave Idle current 0.55 A Efficiency 92 % Cooling system Fon USE port 5V/2A (OC 3.0 - 18W) Protection UP/OUP/OUP/OUT/SCP Protection against inverse polarity Fuse Usage Kitchen equi pment: frigge, microwave, blender, coffer machine, kettle, freezer, oven office equipment: laptop, computer, printer Other, power tools, hoover, hair dryer, fan, TV, games console, radio, music equipment, solar panels, boat arising, air roofficioning, CO cooler Material Alaminium Operating temperature -10°C - 450°C Storage temperature -30°C do +70°C Additional information 20 not cover the wertlation holes of the device Remember to connect the wires and polarity of the power supply veltage correctly 1 soft start function 30°C do +70°C Direction Start function 21 x Newster Levilles in holes of the device Rectage contents 1 x Newster Levilles in holes of the device Rectage contents 2 x Newster Levilles in holes of the device Package depth / length firm) 250 Package depth / length firm) 250 Package length firm) 250	Output voltage	230 V
Efficiency 92% Cooling system Fan USB port 5V/2A (CC 3.0 - 18W) Protection against inverse polarity Fuse Protection against April Against April Against Apr	Output frequency	50 HZ
Efficiency 92*4 Cooling system 50°/24 (OC 3.0 - 18W) USB port 50°/24 (OC 3.0 - 18W) Protection USP/OVP/OEP/OEP/SEP Protection against inverse polarity Fuse Usage Kitchen equipment fridge, microwave, blender, coffee machine, kettle, freezer, oven Office quipment shorter, compute, printer Office quipment, solar panels, boat charging, air conditioning, CO cooker Material Aluminum Operating temperature 10°C + 50°C Storage temperature 20°C 40°C Additional information 20°C 40°C Dimensions (D/L x W x H) 20°C 30°C 30°C 30°C Package contents 1 x Inverter 4 x Fuse 1 x Worming see 1 x Worming se	Waveform	Pure sine wave
Cooling system Fan SYZA (CG 3.0 - 18W) Protection UVP/OVP/OTP/SCP Protection against inverse polarity Fuse Usage Richard Requipment fridge, microwave, blender, coffee machine, kettle, freezer, oven Office equipment beptop, computer, printer Office equipment, solar panels, boat charging, air conditioning, CO cooker Material Aluminium - 10°C - 45°C Storage temperature - 10°C - 45°C Storage temperature - 30°C do 47°C Additional information Description of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soir start function Dimensions (D/L x W x H) - 20°x 330 x 90 mm Package contents	Idle current	0.55 A
USB port 5V/ZA (QC 3.0 - 18W) Protection UVP/OVP/OCP/OTP/SCP Protection against inverse polarity Fuse Usage Kitchen equipment: Indige, microwave, blender, coffee machine, kettle, freezer, oven Office equipment: object, computer, printer Other power tools, hower, hard rider, fan, TiV, games console, radio, music equipment, solar panels, boat charging, air conditioning, CO cooker Material Aluminium Operating temperature -10°C - 450°C Storage temperature -30°C do +70°C Additional information Do not cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Dimensions (D/L x Wx H) 210 x 330 x 90 mm Package contents 1 x Inverter 4 x Fuse 1 x Wounting key 1 x Wou	Efficiency	92 %
Protection UVP/OVP/OTP/SCP Protection against inverse polarity Fuse Kitchen equipment fridge, microwave, blender, coffee machine, kettle, freezer, oven Office equipment laptop, computer, printer Office equipment, solar panels, boat charging, air conditioning, CO cooker Material Aluminium Operating temperature -10°C ~ +50°C Storage temperature -50°C do +70°C Additional information Do not cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function Dimensions (D/L x W x H) 210 x 330 x 90 mm Package contents 1 x Inverter 4 x F use 1 x Mounting key 1 x Warranty card 1 x Operating instructions Package depth / length [mm] 250 Package width [mm] 390 Package width [mm] 150 Net weight [kg] 4,700 Crefficate CE Editor To a specific printer of the content of the content of the content of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function 1 x Inverter 4 x F use 1 x Mounting key 1 x Wirring set 1 x Mounting key 1 x Warranty card 1 x Operating instructions Package height [mm] 390 Package height [mm] 150 Net weight [kg] 4,700 Crefficate CE Editor To a point of the content of the content of the device Remember connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function holes of the device Remember to connect the wires and polarity of the p	Cooling system	Fan
Protection against inverse polarity Fuse	USB port	5V/2A (QC 3.0 - 18W)
Usage Contents C	Protection	UVP/OVP/OCP/OTP/SCP
Office equipment: laptop, computer, printer Other, power tools, hoover, har dryer, fan, TV, games console, radio, music equipment, solar panels, boat charging, air conditioning, CO cooker Material Aluminium Operating temperature -10°C ~ 50°C Storage temperature -30°C do +70°C Additional information Do not cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function Dimensions (D/L x W x H) 210 x 330 x 90 mm Package contents 1 x Inverter 4 x Fuse 1 x Mounting key 1 x Warranty card 1 x Mounting key 1 x Warranty card 1 x Mounting key 1 x Warranty card 1 x Operating instructions Package depth / length [rmm] 390 Package width [rmm] 150 Net weight [kg] 4.700 Certificate CE	Protection against inverse polarity	Fuse
Operating temperature 5 torage temperature Additional information Do not cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function Dimensions (D/L x W x H) 2 10 x 330 x 90 mm 1 x Inverter 1 x Wuring set 1 x Wuring	Usage	Office equipment: laptop, computer, printer Other: power tools, hoover, hair dryer, fan, TV, games console, radio, music equipment, solar panels, boat
Storage temperature Additional information Dimensions (D/L x W x H) Package contents Auxiliary (250 Package depth / length [mm] Package width [mm] Package height [mm] Package height [kg] Net weight [kg] CE 230°C do +70°C Aon't Cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function 1 x Inverter 4 x F use 1 x Wiring set 1 x Wounting key 1 x Warranty card 1 x Operating instructions Package width [mm] 250 Package width [mm] 150 Net weight [kg] 4.100 Ceross weight [kg] CE	Material	Aluminium
Additional information Do not cover the ventilation holes of the device Remember to connect the wires and polarity of the power supply voltage correctly! Dimensions (D/L x W x H) 210 x 330 x 90 mm 1 x Inverter 4 x F use 1 x Wounting key 1 x Warranty card 1 x Nounting key 1 x Warranty card 1 x Operating instructions Package depth / length [mm] 250 Package width [mm] 390 Package height [mm] 150 Net weight [kg] 4.100 Cross weight [kg] 4.700 Cetificate CE	Operating temperature	-10°C ~ +50°C
Remember to connect the wires and polarity of the power supply voltage correctly! Soft start function Dimensions (D/L x W x H) 210 x 330 x 90 mm Package contents I x Inverter 4 x F Use 1 x Wiring set 1 x Wounting key 1 x Warranty card 1 x Operating instructions Package depth / length [mm] 250 Package width [mm] 390 Package height [mm] 150 Net weight [kg] 4,100 Gross weight [kg] 4,700 Cetificate CE	Storage temperature	-30°C do +70°C
Package contents \$\begin{array}{c} 1 \times 1 \times 4 \	Additional information	Remember to connect the wires and polarity of the power supply voltage correctly!
4x Fuse 1x Wiring set 1x Mounting key 1x Warranty card 1x Operating instructions Package depth / length [mm] 250 Package width [mm] 390 Package height [mm] 150 Net weight [kg] 4.100 Gross weight [kg] 4.700 Certificate CE	Dimensions (D/L x W x H)	210 x 330 x 90 mm
Package width [mm] 390 Package height [mm] 150 Net weight [kg] 4.100 Gross weight [kg] 4.700 Certificate CE	Package contents	4 x Fuse 1 x Wiring set 1 x Mounting key 1 x Warranty card
Package height [mm] 150 Net weight [kg] 4.100 Gross weight [kg] 4.700 Certificate CE	Package depth / length [mm]	250
Net weight [kg] 4.100 Gross weight [kg] 4.700 Certificate CE	Package width [mm]	390
Gross weight [kg] 4.700 Certificate CE	Package height [mm]	150
Certificate CE	Net weight [kg]	4.100
	Gross weight [kg]	4.700
Warranty 24 month	Certificate	CE
	Warranty	24 month
EAN code 5901878519395	EAN code	5901878519395

WWW.QOLTEC.COM 5 / 5

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Inverters category:

Click to view products by **QOLTEC** manufacturer:

Other Similar products are found below:

PV-400FC PV550 SOLAR BOOST MPPT-3000 PRO UPS-2000SR UPS-4000SR UPS-1200SR 3SPS200012 3SPS500048 SINUS PRO 2000 E 12/230V SINUS PRO 3000 E 48/230V 51933 POWER SINUS 3000 12/230V 51925 51924 NTU-2200-224EU NTS-2200-224EU NTS-750-212EU 53875 ISI-501-224EU 3IPSMPPT09 51928 53887 NTS-1200-224EU 51927 51936 IPS-4000S 12V/230V IPS-3000S 12V/230V IPS-3000S 24V/230V IPS-4000S 24V/230V GREEN BOOST MPPT 3000 51934 51939 NTU-2200-248EU ISI-501-248EU NTU-1200-212EU NTU-2200-212EU 3IPSMPPT41 53876 53886 51932 51926 NTS-750-224EU 51938 SINUS600 24V PE-35 PE-40 PS-250 3IPS100012 TS-1500-224B ISI-500-148A