



Uninterruptible Power Supply | Monolith | 2000VA | 1200W | LCD | USB

Product code: 53956

UPS line interactive UPS Qoltec is a modern and economical device that ensures stable operation of connected electronic devices even in the event of a power failure. The duration of a power supply with a 100W load is 55 minutes. The UPS protects connected devices against loss and voltage drop in the network and excludes the possibility of damage in the event of overvoltages in the electricity network, also protects against overloads and short circuits. The Qoltec offline UPS will meet the requirements of anyone who wants to have control over the stable operation of their devices regardless of fluctuations in the mains supply. Thanks to the highest quality and wide range of operation, it is an ideal solution for powering desktops and other peripheral devices at home or in the enterprise, as well as in educational institutions and offices.

TECHNICAL DATA

| | |
|----------------------------|--|
| WAVE FORM | Modified sine wave |
| RUNTIME (100W) | 55 min |
| USABLE POWER | 1200 W |
| RATED CAPACITY | 2000 VA |
| LOAD TYPE | Personal computer and other PC peripheral devices, payment terminals, small security devices |
| AC VOLTAGE RANGE | 140Vac ~ 290Vac |
| AC FREQUENCY | 50Hz 10% |
| OUTPUT RANGE (LINE) | 220Vac 10% |
| OUTPUT FREQUENCY (LINE) | 50Hz 10% |
| OUTPUT VOLTAGE (BATTERY) | 220Vac ~ 230Vac 5% |
| OUTPUT FREQUENCY (BATTERY) | 50Hz - 60Hz 1Hz |
| TRANSFER TIME | 2-6 ms |
| OUTPUT SOCKETS | 1 x FRENCH 1 x SCHUKO 1 x IEC 1 x RJ45 1 x USB type B |
| BUILT-IN BATTERY | 2x12V/9Ah |
| SCREEN | LCD |
| CHARGING TIME | 6 hrs to reach 90% capacity |

| | |
|--------------------------------|---|
| STORAGE TEMPERATURES | -15°C to 45°C |
| OPERATING TEMPERATURE | 0 C to +40 C |
| ENVIRONMENT HUMIDITY | 0% - 95% |
| RELATIVE HUMIDITY | 0% - 90% |
| SAFETY | <ul style="list-style-type: none"> Overload protection Short Circuit Protection Overheat Protection Under/Overvoltage Protection Input Fuses Protection |
| USAGE | Home offices |
| ADDITIONAL INFORMATION | <ul style="list-style-type: none"> Line- Interactive model USB port (communication with PC) Intelligent automatic AVR function Automatic mute Compact size and ergonomic design: it can be placed on a desktop or other convenient location Perfect protection for overload, short circuit, over voltage, low voltage and overheating Excellent microprocessor control optimizes reliability The fastest charging capacity Eco friendly and user friendly Low maintenance cost Wide input range Easy installation |
| PACKAGE CONTENTS | <ul style="list-style-type: none"> UPS with built-in power cable (1 x FRENCH) 1.2m User manual |
| NOISE | Less than 40dB |
| COMMUNICATION INTERFACE | USB |
| DIMENSIONS | 370 x 135 x 165 mm |
| WEIGHT | 11.3 kg |
| WARRANTY | 24 months |
| EAN CODE | 5901878539560 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switching Power Supplies](#) category:

Click to view products by [QOLTEC](#) manufacturer:

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [AAD600S-4-OP](#) [R22095](#) [HWS50A-5/RA](#) [KD0204](#) [9021](#) [S-15F-12](#) [LDIN100150](#) [LPM000-BBAR-01](#) [LPX17S-C](#)
[EVS57-10R6/R](#) [FDC40-24S12](#) [FP80](#) [FRV7000G](#) [22929](#) [CQM1IA121](#) [40370121900](#) [VI-PU22-EXX](#) [40370121910](#) [LDIN5075](#)
[432703037161](#) [WRB01X-U](#) [LPX140-C](#) [08-30466-1040G](#) [09-160CFG](#) [70841004](#) [70841025](#) [VPX3000-CBL-DC](#) [LPM000-BBAR-05](#)
[LPM000-BBAR-08](#) [LPM124-OUTA1-48](#) [LPM000-BBAR-07](#) [LPM109-OUTA1-10](#) [LPM616-CHAS](#) [08-30466-1055G](#) [08-30466-2175G](#)
[DMB-EWG](#) [TVQF-1219-18S](#) [6504-226-2101](#) [CQM1IPS01](#) [XPFM201A+](#) [MAP80-4000G](#) [LFP300F-24-TY](#) [SMP21-L20-DC24V-5A](#) [VI-](#)
[MUL-ES](#) [08-30466-0065G](#) [CME240P-24](#) [VI-RU031-EWWX](#) [08-30466-0028G](#)