


# TGA4533-SM

## K-Band Power Amplifier



### Applications

- Point-to-Point Radio
- K-Band Sat-Com




QFN 4x4 mm 20L

### Product Features

- Frequency Range: 21.2 – 23.6 GHz
- Power: 32 dBm Psat, 31 dBm P1dB
- Gain: 22 dB
- TOI: 41 dBm at 21 dBm SCL
- NF: 6 dB
- Integrated Power Detector
- Bias:  $V_d = 6\text{ V}$ ,  $I_{dq} = 880\text{ mA}$ ,  $V_g = -0.7\text{ V}$  Typical
- Package Dimensions: 4.0 x 4.0 x 0.85 mm

### Functional Block Diagram



### General Description

The TriQuint TGA4533-SM is a K-Band Power Amplifier. The TGA4533-SM operates from 21.2 – 23.6 GHz and is designed using TriQuint's power pHEMT production process.

The TGA4533-SM typically provides 31 dBm of output power at 1dB gain compression with small signal gain of 22 dB. Third Order Intercept is 41 dBm at 21 dBm SCL.

The TGA4533-SM is available in a low-cost, surface mount 20 lead 4x4 QFN package. It is ideally suited for Point-to-Point Radio, and K-Band Sat-Com.

Lead-free and RoHS compliant

Evaluation Boards are available upon request.

### Pin Configuration

| Pin #                             | Symbol    |
|-----------------------------------|-----------|
| 1, 3, 4, 5, 6, 10, 11, 13, 14, 20 | N/C       |
| 2                                 | RF IN     |
| 7, 19                             | $V_g$     |
| 8, 18                             | GND       |
| 12                                | RF OUT    |
| 9, 17                             | $V_d$     |
| 15                                | $V_{det}$ |
| 16                                | $V_{ref}$ |

### Ordering Information

| Part No.   | ECCN  | Description            |
|------------|-------|------------------------|
| TGA4533-SM | EAR99 | K-Band Power Amplifier |

Standard T/R size = 500 pieces on a 7" reel.

### Specifications

#### Absolute Maximum Ratings

| Parameter                            | Rating         |
|--------------------------------------|----------------|
| Drain Voltage, Vd                    | +6.5 V         |
| Gate Voltage, Vg                     | -3 to 0 V      |
| Drain to Gate Voltage, Vd – Vg       | 10 V           |
| Drain Current, Id                    | 2 A            |
| Gate Current, Ig                     | -8.8 to 113 mA |
| Power Dissipation, P <sub>diss</sub> | 12.7 W         |
| RF Input Power, CW, T = 25°C         | 26 dBm         |
| Channel Temperature, T <sub>ch</sub> | 200 °C         |
| Mounting Temperature (30 Seconds)    | 260 °C         |
| Storage Temperature                  | -40 to 150 °C  |

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

#### Recommended Operating Conditions

| Parameter                 | Min | Typical | Max | Units |
|---------------------------|-----|---------|-----|-------|
| Vd                        |     | 6       |     | V     |
| Idq                       |     | 880     |     | mA    |
| Id_drive (Under RF Drive) |     | 1300    |     | mA    |
| Vg                        |     | -0.7    |     | V     |

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

#### Electrical Specifications


Test conditions unless otherwise noted: 25 °C, Vd = 6 V, Idq = 880 mA, Vg = -0.7 V Typical.

| Parameter   | Min  | Typical | Max  | Units |
|---|------|---------|------|-------|
| Operational Frequency Range                           | 21.2 |         | 23.6 | GHz   |
| Gain  | 19   | 22      |      | dB    |
| Input Return Loss, IRL                                |      | 10      |      | dB    |
| Output Return Loss, ORL                               |      | 10      |      | dB    |
| Output Power @ Saturation, P <sub>sat</sub>           | 30   | 32      |      | dBm   |
| Output Power @ 1dB Gain Compression, P <sub>1dB</sub> | 28   | 31      |      | dBm   |
| Output Third Order Intercept, TOI                     | 38.5 | 41      |      | dBm   |
| Noise Figure, NF                                      |      | 6       |      | dB    |
| Gain Temperature Coefficient                          |      | -0.025  |      | dB/°C |
| Power Temperature Coefficient                         |      | -0.015  |      | dB/°C |







### Specifications (cont.)

### Thermal and Reliability Information







| Parameter  | Condition   | Rating                             |
|--|---|------------------------------------|
| Thermal Resistance, $\theta_{JC}$ , measured to back of package    | Tbase = 85 °C   | $\theta_{JC} = 9.0$ °C/W           |
| Channel Temperature (Tch), and Median Lifetime (Tm)                | Tbase = 85 °C, Vd = 6 V, Idq = 880 mA, Pdiss = 5.28 W               | Tch = 133 °C<br>Tm = 7.4 E+6 Hours |
| Channel Temperature (Tch), and Median Lifetime (Tm) Under RF Drive | Tbase = 85 °C, Vd = 6 V, Id = 1300 mA, Pout = 31 dBm, Pdiss = 6.2 W | Tch = 144 °C<br>Tm = 2.0 E+6 Hours |









### Typical Performance







### Typical Performance (cont.)




### Typical Performance (cont.)



### Typical Performance (cont.)



### Application Circuit




Vg can be biased from either side (pin 7 or pin 19), and the non-biased side can be left open.  
 Vd must be biased from both sides (pin 9 and pin 17).

| Bias-up Procedure   | Bias-down Procedure                  |
|---|--------------------------------------|
| Vg set to -1.5 V  | Turn off RF supply                   |
| Vd set to +6 V  | Reduce Vg to -1.5V. Ensure Id ~ 0 mA |
| Adjust Vg more positive until quiescent Id is 880 mA.<br>This will be ~ Vg = -0.7 V typical | Turn Vd to 0 V                       |
| Apply RF signal to RF Input   | Turn Vg to 0 V                       |



### Pin Description



| Pin                               | Symbol           | Description   |
|-----------------------------------|------------------|---|
| 1, 3, 4, 5, 6, 10, 11, 13, 14, 20 | N/C              | No internal connection; must be grounded on PCB   |
| 2                                 | RF IN            | Input, matched to 50 ohms   |
| 7, 19                             | V <sub>g</sub>   | Gate voltage. Bias network is required; can be biased from either pin, and non-biased pin can be left opened; see Application Circuit on page 8 as an example.  |
| 8, 18                             | GND              | Internal grounding; can be grounded or left open on PCB   |
| 12                                | RF OUT           | Output, matched to 50 ohms  |
| 9, 17                             | V <sub>d</sub>   | Drain voltage. Bias network is required; must be biased from both pins; see Application Circuit on page 8 as an example.  |
| 15                                | V <sub>det</sub> | Detector diode output voltage. Varies with RF output power.   |
| 16                                | V <sub>ref</sub> | Reference diode output voltage.   |
| 21                                | GND              | Backside Paddle. Multiple vias should be employed to minimize inductance and thermal resistance; see Mounting Configuration on page 12 for suggested footprint. |



### Applications Information

#### PC Board Layout

Top RF layer is 0.008” thick Rogers RO4003,  $\epsilon_r = 3.38$ . Metal layers are 0.5-oz copper. Microstrip 50  $\Omega$  line detail: width = 0.0175”.

The pad pattern shown has been developed and tested for optimized assembly at TriQuint Semiconductor. The PCB land pattern has been developed to accommodate lead and package tolerances. Since surface mount processes vary from company to company, careful process development is recommended.

For further technical information, refer to the [TGA4533-SM](#) Product Information page.




#### Bill of Material

| Ref Des        | Value    | Description               | Manufacturer | Part Number |
|----------------|----------|---------------------------|--------------|-------------|
| C1, C2, C3, C4 | 100 pF   | Cap, 0402, 50 V, 5%, COG  | various      |             |
| C5, C6, C7     | 1 uF     | Cap, 0603, 25 V, 10%, X5R | various      |             |
| R1             | 15 Ohms  | Res, 0402, 0.1 W, 5%, SMD | various      |             |
| R2, R3         | 40K Ohms | Res, 0603, 0.1 W, 5%, SMD | various      |             |

### Mechanical Information

### Package Information and Dimensions

All dimensions are in millimeters.



This package is lead-free/RoHS-compliant. The package base is copper alloy and the plating material on the leads is NiPdAu. It is compatible with both lead-free (maximum 260 °C reflow temperature) and tin-lead (maximum 245 °C reflow temperature) soldering processes.

The TGA4533-SM will be marked with the “4533” designator and a lot code marked below the part designator. The “YY” represents the last two digits of the year the part was manufactured, the “WW” is the work week, and the “XXXX” is an auto-generated number.


### Mechanical Information (cont.)

#### Mounting Configuration

All dimensions are in millimeters (inches).


Notes:

1. A heatsink underneath the area of the PCB for the mounted device is recommended for proper thermal operation.
2. Ground / thermal vias are critical for the proper performance of this device. Vias have a final plated thru diameter of 0.254 mm (0.010").



### Tape and Reel Information

Tape and reel specifications for this part are also available on the TriQuint website in the “Application Notes” section.  
 Standard T/R size = 500 pieces on a 7 x 0.5” reel.



### CARRIER AND COVER TAPE DIMENSIONS

| Part                        | Feature                                | Symbol | Size (in) | Size (mm) |
|-----------------------------|--|--------|-----------|-----------|
| Cavity                      | Length                                 | A0     | 0.171     | 4.35      |
|                             | Width                                  | B0     | 0.171     | 4.35      |
|                             | Depth                                  | K0     | 0.043     | 1.1       |
|                             | Pitch                                  | P1     | 0.315     | 8.0       |
| Distance Between Centerline | Cavity to Perforation Length Direction | P2     | 0.079     | 2.0       |
|                             | Cavity to Perforation Width Direction  | F      | 0.217     | 5.5       |
| Cover Tape                  | Width                                  | C      | 0.374     | 9.5       |
| Carrier Tape                | Width                                  | W      | 0.472     | 12.0      |

### Product Compliance Information

#### ESD Information



**Caution! ESD-Sensitive Device**

ESD Rating: Class 1A  
 Value:  $\geq 250V$  and  $\leq 500V$   
 Test: Human Body Model (HBM)  
 Standard: JEDEC Standard JESD22-A114

#### MSL Rating

Level 1 at +260 °C convection reflow  
 The part is rated Moisture Sensitivity Level 1 at 260°C per JEDEC standard IPC/JEDEC J-STD-020.

#### ECCN

US Department of Commerce EAR99

#### Solderability


Compatible with the latest version of J-STD-020, Lead free solder, 260°

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free

### Recommended Soldering Temperature Profile



# TGA4533-SM

## K-Band Power Amplifier



### Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: [www.triquint.com](http://www.triquint.com)  
Email: [info-sales@tqs.com](mailto:info-sales@tqs.com)

Tel: +1.972.994.8465  
Fax: +1.972.994.8504

For technical questions and application information:

Email: [info-networks@tqs.com](mailto:info-networks@tqs.com)

### Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright © 2015 TriQuint Semiconductor, Inc. All rights reserved.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Amplifier](#) category:*

*Click to view products by [Qorvo](#) manufacturer:*

Other Similar products are found below :

[A82-1](#) [BGA622H6820XTSA1](#) [BGA 728L7 E6327](#) [BGB719N7ESDE6327XTMA1](#) [HMC397-SX](#) [HMC405](#) [HMC561-SX](#) [HMC8120-SX](#)  
[HMC8121-SX](#) [HMC-ALH382-SX](#) [HMC-ALH476-SX](#) [SE2433T-R](#) [SMA3101-TL-E](#) [SMA39](#) [A66-1](#) [A66-3](#) [A67-1](#) [LX5535LQ](#) [LX5540LL](#)  
[MAAM02350](#) [HMC3653LP3BETR](#) [HMC549MS8GETR](#) [HMC-ALH435-SX](#) [SMA101](#) [SMA32](#) [SMA411](#) [SMA531](#) [SST12LP17E-XX8E](#)  
[SST12LP19E-QX6E](#) [WPM0510A](#) [HMC5929LS6TR](#) [HMC5879LS7TR](#) [HMC1126](#) [HMC1087F10](#) [HMC1086](#) [HMC1016](#) [SMA1212](#)  
[MAX2689EWS+T](#) [MAAMSS0041TR](#) [MAAM37000-A1G](#) [LTC6430AIUF-15#PBF](#) [CHA5115-QDG](#) [SMA70-2](#) [SMA4011](#) [A231](#) [HMC-](#)  
[AUH232](#) [LX5511LQ](#) [LX5511LQ-TR](#) [HMC7441-SX](#) [HMC-ALH310](#)