

### Product Overview

The TQQ7101 is an exceptionally high performance BAW duplexer for LTE Band 1. This filter is housed in a compact 3.0 mm x 3.0 mm package for base station applications.


Low insertion loss, coupled with high attenuation makes this filter an ideal choice for small cell BTS needs.

The TQQ7101 is part of Qorvo's extensive portfolio of RF BAW and SAW filters.



6 Pin 3.0 x 3.0 mm leadless SMT Package

### Functional Block Diagram



### Pin Configuration

Pin No.	Label
1, 3, 5	Ground
2	ANT
4	Downlink
6	Uplink

### Key Features

- 60 MHz Bandwidth
- High Attenuation
- Low Loss
- No External Matching Required
- Small Size: 3.00 mm x 3.00 mm x 1.02 mm
- Surface Mount Package
- RoHS Compliant, Pb-Free

### Applications

- Band 1 Duplexer for Small cell BTS
- Base Station Infrastructure
- Small Cells
- Repeaters
- General Purpose Wireless

### Ordering Information

Part No.	Description
TQQ7101	Band 1 Duplexer
TQQ7101EVB	Evaluation Board

## Absolute Maximum Ratings

Parameter	Rating
Storage Temperature	-40 to +125°C
Operation Temperature	-20 to +85°C

## Life Test

Conditions	Rating
+30 dBm DL, +85°C, FD-LTE, 5MHz 16QAM, PAR =8dB	> 87,600 hours
+23 dBm UL, +85°C, CW	> 87,600 hours

Electrical specifications are measured at specified test conditions.

## Electrical Specifications – Downlink <sup>(1)</sup>

Operating Temperature Range: -20 to +85 °C

Parameter	Conditions	Min	Typ	Max	Units
Passband		2110	-	2170	MHz
Insertion Loss <sup>(2)</sup>	2110 – 2170 MHz	-	2.8	3.8	dB
Amplitude Variation	2110 – 2170 MHz (+25 °C)	-	1.2	2.0	dB
Return Loss <sup>(2)</sup>	Antenna Port	7.1	10.2	-	dB
Return Loss <sup>(2)</sup>	Downlink Port	7.7	10.8	-	dB
Attenuation	0.009 – 1920 MHz	36	37	-	dB
	1920 – 1980 MHz	44	47	-	
	1980 – 2025 MHz	36	40	-	
	2025 – 2070 MHz	37	40	-	
	2210 – 2300 MHz	22	47	-	
	2300 – 2370 MHz	48	51	-	
	2370 – 2484 MHz	44	45	-	
	2484 – 2690 MHz	41	42	-	
	2690 – 3400 MHz	35	38	-	
	3400 – 4200 MHz	24	26	-	
4200 – 4400 MHz	35	39	-		
5150 – 5850 MHz	32	34	-		
Harmonic Distortion <sup>(3)</sup>	Pin = +29 dBm	50	55	-	dBc
Channel Power	LTE 5 MHz, PAR = 8dB, 8 years, 85 °C	+29	-	-	dBm

### Notes:

- All specifications are based on the Qorvo schematic for the main reference design.
- Average value over the indicated band.
- Additional 2nd harmonic improvement can be achieved using appropriate application. Refer to product technical notes for details.

## Electrical Specifications – Uplink <sup>(1)</sup>

Operating Temperature Range: -20 to +85 °C

Parameter	Conditions	Min	Typ	Max	Units
Passband		1920		1980	dB
Insertion Loss <sup>(2)</sup>	1920 – 1980 MHz	-	3.1	3.7	dB
Amplitude Variation	1920 – 1980 MHz (+25 °C)	-	1.3	1.9	dB
Return Loss <sup>(2)</sup>	Antenna Port	8.0	10.4	-	dB
Return Loss <sup>(2)</sup>	Uplink Port	7.3	8.6	-	dB
Attenuation	0.009 – 1880 MHz	37	38	-	dB
	1880 – 1900 MHz	34	44	-	
	2000 – 2010 MHz	4	21	-	
	2010 – 2110 MHz	33	37	-	
	2110 – 2690 MHz	38	39	-	
	2690 – 3400 MHz	32	36	-	
	3400 – 3800 MHz	33	35	-	
3800 – 5850 MHz	16	21	-		
Channel Power	CW, 8 years, 85 °C	+23	-	-	dBm

Notes:

1. All specifications are based on the Qorvo schematic for the main reference design.
2. Average value over the indicated band.

## Electrical Specifications – Isolation Uplink to Downlink <sup>(1)</sup>



Operating Temperature Range: -20 to +85 °C

Parameter	Conditions	Min	Typ	Max	Units
Isolation in Uplink <sup>(2)</sup>	1920 – 1980 MHz	48	51	-	dB
Isolation in Downlink <sup>(2)</sup>	2110 – 2170 MHz	39	42	-	dB

Notes:

1. All specifications are based on the Qorvo schematic for the main reference design.
2. Average value over the indicated band.

**TQQ7101EVB Evaluation Board**







**Bill of Material – TQQ7101EVB**


Reference Des.	Value	Description	Manuf.	Part Number
U1	n/a	Band 1 BAW Duplexer	Qorvo	TQQ7101
n/a	n/a	Printed Circuit Board	Qorvo	1039708
n/a	n/a	SMA Edge Connector		1041120

**Performance Plots – Downlink**


Test conditions unless otherwise noted: Temp= +25°C



**Downlink Path - Ant Port Impedance**







**Downlink Port Impedance**




**Performance Plots – Uplink**


Test conditions unless otherwise noted: Temp= +25°C



**Uplink Path - Ant Port Impedance**





**Uplink Port Impedance**



Performance Plots – (cont'd)


Test conditions unless otherwise noted: Temp= +25°C



**Package Marking and Dimensions**

**Package Marking**

Product Identifier: 7101  
 Trace Code: XXXX




**Notes:**

1. All dimensions are in millimeters. Angles are in degrees.
2. Dimension and tolerance formats conform to ASME Y14.4M-1994.
3. The terminal #1 identifier and terminal numbering conform to JESD 95-1 SPP-012.




**PCB Mounting Pattern**



**RECOMMENDED  
 LAND PATTERN**

Top view recommended land pattern metallization.



**RECOMMENDED  
 LAND PATTERN MASK**


Top view recommended land pattern stencil aperture.

**Notes:**


1. All dimensions are in millimeters. Angles are in degrees.
2. Use 1 oz. copper minimum for top and bottom layer metal.

Tape and Reel Information – Carrier and Cover Tape Dimensions

Tape and reel specifications for this part are also available on the Qorvo website.  
Standard T/R size = 2500 pieces on a 7” reel.




Feature	Measure	Symbol	Size (in)	Size (mm)
Cavity	Length	A0	0.132	3.35
	Width	B0	0.132	3.35
	Depth	K0	0.051	1.30
	Pitch	P1	0.157	4.00
Centerline Distance	Cavity to Perforation - Length Direction	P2	0.079	2.00
	Cavity to Perforation - Width Direction	F	0.138	3.50
Cover Tape	Width	C	0.213	5.40
Carrier Tape	Width	W	0.315	8.00



**Tape and Reel Information – Reel Dimensions**

Tape and reel specifications for this part are also available on the Qorvo website.  
 Standard T/R size = 2,500 pieces on a 7" reel.



Feature	Measure	Symbol	Size (in)	Size (mm)
Flange	Diameter	A	6.969	177.0
	Thickness	W2	0.559	14.2
	Space Between Flange	W1	0.346	8.8
Hub	Outer Diameter	N	2.283	58.0
	Arbor Hole Diameter	C	0.512	13.0
	Key Slit Width	B	0.079	2.0
	Key Slit Diameter	D	0.787	20.0

## Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1B	ESDA / JEDEC JS-001-2012
ESD – Charged Device Model (CDM)	Class C3	ESDA / JEDEC JS-002-2014
MSL – Moisture Sensitivity Level	Level 3	IPC/JEDEC J-STD-020



Caution!  
ESD-Sensitive Device

## Solderability

Compatible with both lead-free (260°C max. reflow temp.) and tin/lead (245°C max. reflow temp.) soldering processes. Solder profiles available upon request.

Contact plating: Au over Ni

## RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free



## Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: [www.qorvo.com](http://www.qorvo.com)

Tel: 1-844-890-8163

Email: [customer.support@qorvo.com](mailto:customer.support@qorvo.com)

## Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2016 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Signal Conditioning](#) category:*

*Click to view products by [Qorvo](#) manufacturer:*

Other Similar products are found below :

[MAPDCC0001](#) [MAPDCC0004](#) [PD0409J5050S2HF](#) [880157](#) [HHS-109-PIN](#) [DC1417J5005AHF](#) [AFS14A30-2185.00-T3](#) [AFS14A35-1591.50-T3](#) [DS-323-PIN](#) [B39321R801H210](#) [1A0220-3](#) [JP510S](#) [LFB212G45SG8C341](#) [LFB322G45SN1A504](#) [LFL182G45TC3B746](#) [SF2159E](#) [30057](#) [FM-104-PIN](#) [CER0813B](#) [MAPDCC0005](#) [3A325](#) [40287](#) [41180](#) [ATB3225-75032NCT](#) [BD0810N50100AHF](#) [BD2425J50200AHF](#) [C5060J5003AHF](#) [JHS-115-PIN](#) [JP503AS](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [DC3338J5005AHF](#) [43020](#) [LFB2H2G60BB1C106](#) [LFL15869MTC1B787](#) [X3C19F1-20S](#) [XC3500P-20S](#) [10013-20](#) [SF2194E](#) [CDBLB455KCAX39-B0](#) [TGL2208-SM, EVAL](#) [RF1353C](#) [1E1305-3](#) [1F1304-3S](#) [1G1304-30](#) [B0922J7575AHF](#) [2020-6622-20](#) [10017-3](#) [TP-103-PIN](#) [BD1222J50200AHF](#)