
THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.

REVISION						
REV.	DESCRIPTION	DATE	APPROVED			
В	RoHS Compliancy	06-01-06	DP			
C	Updated Specifications	08-31-11	LY			

	51.5 ± 1.0
65.0 ± 1.0	Ø7.6ID Ø13.5



NOTES:

MATERIAL:

MOULDING: NYLON, FLAMMABILITY RATING UL94V-0

CONTACTS: BRASS, CLEAN

RATING: 10A 250V AC

INSULATION RESISTANCE: >1000 M OHM CONTACT RESISTANCE: < 10m OHM

A.C. BREAKDOWN: POLE-POLE: 4.5kV POLES-ACCESSIBLE: 4kV

OPERATING TEMPERATURE: -40° C TO +70° C

WITHDRAWL FORCE: 10N (MIN), 50N (MAX)

APPROVALS: UL,CSA,VDE

FOR USE WITH 18 AWG CORDAGE ONLY

RoHS COMPLIANT

CONTROLLED

Dim range	Tolerance +/- (mm)	Qualtek Electronics Corp. PPC DIVISION			
(mm)		Part Number:	705-00/00	RoHS Compliant	
0-1	0.15	Description: REWIRABLE PLUG ASSEMBLY			
1-6	0.20				
6-18	0.30			DE1/ 6	
18-50	0.50		UNIT: mm	REV. C	
50-120	0.70	Drawn / Date	Checked / Date	Approved / Date	
120-250	0.90	B.Zhang	12-30-02	JJH / 12-30-02	
250-500	1.20	12-30-02			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Entry Modules category:

Click to view products by Qualtek manufacturer:

Other Similar products are found below:

0098.0050 6167.0002 6609100-2 7-6609955-2 FKI2-50-6/M5 FN361-6-06 FN389-4-22 FN9226B-6-02 FN9233S1-10-06 FN9233S1-8-06 FN9233S1B-8-06 FN9233S1R-1-06 FN9233S1R-12-06 FN9233SB-1-06 FN9233SB-12-06 FN9233SB-8-06 FN9233SR-10-06 FN9244B-15-06HI FN9244EB-3-06 FN9244EB-8-06 FN9244ER-15-06 FN9244ER-8-06 FN9244ES1-8-06 FN9244ESB-8-06 FN924ESB-8-06 FN924ESB