

PAGE 1/1	ISSUE <b>12/07/2021</b>	SERIES <b>TestPro Cable</b>	PART NUMBER <b>1801211210914GX</b>
----------	-------------------------	-----------------------------	------------------------------------

All dimensions are in mm  
For more details, please see connectors TDS



**DESIGNATION**

Cable	<b>Armoured measurement cable - P/N - TestPro 3</b>
Connector Left	<b>N 18 - straight plug - Passivated stainless steel - P/N: R163063101</b>
Connector Right	<b>N 18 - straight plug - Passivated stainless steel - P/N: R163063101</b>
Assembly Length	<b>914 mm / 35.98 inch (tolerance = ± 2%)</b>
Assembly Weight	<b>217.10 gr / 7.66 oz (tolerance = ± 5%)</b>

**ELECTRICAL CHARACTERISTICS**

Characteristic impedance	<b>50 Ohms</b>
Max operating frequency	<b>18.0 GHz</b>
Assembly Typ Insertion Loss	<b>1.94 dB (at 20 °C, at 18.0 GHz )</b>
Assembly Typ VSWR	<b>1.25 (at 18.0 GHz )</b>
Assembly Max. Insertion Loss	<b>2.13 dB (at 20 °C, at 18.0 GHz )</b>
Assembly Max VSWR	<b>1.30 (at 18.0 GHz )</b>
Assembly Max Return Loss	<b>17.7 dB (at 18.0 GHz )</b>
Phase stability vs. Temp	<b>4° / m / GHz (-55° / +100°C)</b>
Dielectric withstanding voltage	<b>1500 V</b>
Insulation resistance	<b>5000 M.Ohms</b>
Other	<b>Amplitude stability typ. (dB) 0,05 @ 40GHz</b> <b>Phase with flexure stability typ. 4,8° @ 40GHz</b> <b>Note: Max IL are indicative only when superior to 40dB</b>

**MECHANICAL CHARACTERISTICS**

Cable Outer diameter	<b>7.29 mm Max   0.287 inch</b>
Static bending radius	<b>25.0 mm   0.98 inch</b>
Dynamic bending radius	<b>50.0 mm   1.97 inch</b>
Other	<b>Flexure life cycle &gt; 20,000</b> <b>Mating cycles durability &gt; 5,000</b>

**ENVIRONMENTAL CHARACTERISTICS**

Temperature range	<b>-55 +125°C</b>
Fire resistance	<b>Yes</b>
RoHS	<b>Yes</b>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Cable Assemblies](#) category:*

*Click to view products by [Radiall](#) manufacturer:*

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [R285001001](#) [R288940004](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#) [24P104C24P1-006](#)  
[24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-50](#) [24P103C24P2-](#)  
[003](#) [25P203C25P2-003](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-COAX1](#) [4814-K-](#)  
[48](#) [115101-09-06.00](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#) [GD0BQ0BQ024.0](#) [1-3636-600-5210](#)  
[TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-1SL-1](#) [PT82NSMA](#) [73-6353-10](#)  
[R285020301W](#) [PCX-18-50](#) [Minibend-9](#) [Minibend-4](#) [BNC TO SMA Cable](#) [MIKROE-274](#)