









Technical Data Sheet

RIGHT ANGLE JACK BULKHEAD P.C.B. MOUNT TAB RECEPTACLE

PAGE 2/2 ISSUE 1412 G SERIES SMA PART NUMBER 9652-1513-003

PACKAGING

1	Contact us	Contact us
Standard	Unit	Other

ELECTRICAL CHARACTERISTICS

 $\begin{array}{ccc} \text{Impedance} & & \textbf{50} & \Omega \\ \text{Frequency} & & \textbf{0-12.4} & \text{GHz} \end{array}$

VSWR *1.10 0.0050 x F(GHz) Maxi Insertion loss 0.1 √F(GHz) dB Maxi - F(GHz)) dB Maxi RF leakage Voltage rating 335 Veff Maxi Dielectric withstanding voltage 750 Veff mini Insulation resistance 5000 $M\Omega$ mini

MECHANICAL CHARACTERISTICS

Center contact retention

Axial force – Mating End N mini
Axial force – Opposite end N mini
Torque N.cm mini

Recommended torque

Mating N.cm Panel nut N.cm

Mating life 500 Cycles mini

Weight **5.7900** g

ENVIRONMENTAL

°C

Atm.cm3/s

Operating temperature -65/+165 Hermetic seal

Panel leakage

SPECIFICATION

OTHER CHARACTERISTICS

Assembly instruction:

Others:

*transmission line only



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Radiall manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N 6500-7071-046 6769 CX050L2AQ 7002-1541-010 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 73404-2300 7405-1521-005 7405-1521-802 8527 8547 FS11V 877931 8808-1511-001 9049-9513-000 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL74C-221 PL75MC-217 PL803-7 1200690078 1-201144-1 R107003010W R110A172100